

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	pb97604	Batch NO. :	LCM2503310
Print Interval :	50000 Tablets	Running Time :	07 Hour 00 Min 07 Sec
Total Counter :	658996	Total Running Time :	2406 Hour 34 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	180	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		660000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	48.20	kN	No		
HEP :	20.0 %	46.27	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	39.33	kN	Yes 20	Times	
Ref :		38.56	kN			
LCP :	2.0 %	37.79	kN	Yes 20	Times	
LEP :	20.0 %	30.85	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	28.92	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.08	kN	Min :	2.01	kN	Punch NO.;	29
		1.30	%	Max :	2.16	kN	Punch NO.;	8
Mean Main Pressure :	SD :	38.79	kN	Min :	37.12	kN	Punch NO.;	41
		1.70	%	Max :	40.11	kN	Punch NO.;	13
Filling Depth :	Increase ;	170	Times	Decrease ;	180	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	27	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.67	mm	Main Thickness ;	3.68	mm
Filling Depth :	10.53	mm	Current Cam :	Cam C	
Main Air pressure :	0.819	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	68	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.17	kN	Max Punch ;	6
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	658996	Tablets			
A.W.C Counter :	657265	Tablets			
HEP :	0 (0%)	Tablets	LEP :	66 (0.0%)	Tablets
GOOD :	657199 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Leveti1000mgSTLC2D00
User ID :	pb97604	Batch NO. :	LCM2503310
Print Interval :	50000 Tablets	Running Time :	07 Hour 00 Min 07 Sec
Total Counter :	658996	Total Running Time :	2406 Hour 34 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	184	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		660000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	50.38	kN	No		
HEP :	20.0 %	48.36	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	41.11	kN	Yes 20	Times	
Ref :		40.30	kN			
LCP :	2.0 %	39.50	kN	Yes 20	Times	
LEP :	20.0 %	32.24	kN	Yes 15	Rotations 20	Tablets
LSP :	25.0 %	30.23	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.24	kN	Min :	2.16	kN	Punch NO.;	11
SD :	1.30	%	Max :	2.32	kN	Punch NO.;	40
Mean Main Pressure :	40.24	kN	Min :	38.49	kN	Punch NO.;	17
SD :	2.00	%	Max :	42.12	kN	Punch NO.;	53
Filling Depth :	Increase ; 122	Times	Decrease ;	167	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.80	mm	Main Thickness ;	3.81	mm
Filling Depth :	10.18	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.819	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	68	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.05	kN	Max Punch ;	53
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.17	kN	Max Punch ;	6
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	658996	Tablets			
A.W.C Counter :	657265	Tablets			
HEP :	0 (0%)	Tablets	LEP :	66 (0.0%)	Tablets
GOOD :	657199 (100.0%)	Tablets			