

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | SERTRA100MG<br>STSH4B00 |
| User ID :        | sj97904       | Batch NO. :          | SHM2503810              |
| Print Interval : | 50000 Tablets | Running Time :       | 00 Hour 57 Min 51 Sec   |
| Total Counter :  | 250208        | Total Running Time : | 2407 Hour 33 Min        |
| Station :        | Station 1     |                      |                         |

### Setting Value

|                                    |             |                   |         |                    |              |           |
|------------------------------------|-------------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 58                | %       | Manual ;           | 20           | RPM       |
| Filling Cam :                      |             | Cam C<br>8.5-14mm |         | Cam Range :        | Min :        | 6.50 mm   |
| Target Quantity :                  |             | 3000000           | Tablets |                    | Max :        | 12.00 mm  |
| Air Pressure Low Limit :           |             | 0.400             | MPa     |                    |              |           |
| Oil Lubrication :                  |             |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 80                | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 30                | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |             | 60.0              | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 1.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 1.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.00              | kN      |                    |              |           |
|                                    |             |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 25.0 %      | 22.20             | kN      | No                 |              |           |
| HEP :                              | 20.0 %      | 21.32             | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %       | 18.12             | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 17.76             | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 17.41             | kN      | Yes 15             | Times        |           |
| LEP :                              | 20.0 %      | 14.21             | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 25.0 %      | 13.32             | kN      | No                 |              |           |
| SD limit :                         | 45.0 %      |                   |         | Yes                |              |           |
| Pre HSP                            |             | 40.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |                   |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | None        |                   |         |                    |              |           |

### Pressure Data

|                      |              |       |              |       |    |            |    |
|----------------------|--------------|-------|--------------|-------|----|------------|----|
| Mean Pre Pressure :  | 1.79         | kN    | Min :        | 1.71  | kN | Punch NO.; | 60 |
| SD :                 | 1.20         | %     | Max :        | 1.84  | kN | Punch NO.; | 40 |
| Mean Main Pressure : | 17.91        | kN    | Min :        | 15.77 | kN | Punch NO.; | 60 |
| SD :                 | 3.20         | %     | Max :        | 19.09 | kN | Punch NO.; | 64 |
| Filling Depth :      | Increase ; 6 | Times | Decrease ; 5 | Times |    |            |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 258720   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 16       | RPM          |
| Pre Upper Punch Position ;    | 3.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 7.00    | mm  | Pre Thickness ;  | 4.00     | mm           |
| Main Upper Punch Position ;   | 3.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.54    | mm  | Main Thickness ; | 2.54     | mm           |
| Filling Depth :               | 7.97    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.830   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 11      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 22      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.49 | kN |             |    |
|                  | Max ;     | 0.67 | kN | Max Punch ; | 30 |
| Lower Punch :    | Average ; | 0.18 | kN |             |    |
|                  | Max ;     | 0.29 | kN | Max Punch ; | 39 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                   |         |       |            |         |
|-----------------|-------------------|---------|-------|------------|---------|
| Total Counter : | 250208            | Tablets |       |            |         |
| A.W.C Counter : | 246274            | Tablets |       |            |         |
| HEP :           | 26 (0.0%)         | Tablets | LEP : | 482 (0.2%) | Tablets |
| GOOD :          | 245766<br>(99.8%) | Tablets |       |            |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | SERTRA100MG<br>STSH4B00 |
| User ID :        | sj97904       | Batch NO. :          | SHM2503810              |
| Print Interval : | 50000 Tablets | Running Time :       | 00 Hour 57 Min 51 Sec   |
| Total Counter :  | 250208        | Total Running Time : | 2407 Hour 33 Min        |
| Station :        | Station 2     |                      |                         |

### Setting Value

|                                    |        |           |         |                    |              |           |
|------------------------------------|--------|-----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 50        | %       | Manual ;           | 21           | RPM       |
| Filling Cam :                      |        | Cam C     |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |        | 8.5-14mm  |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |        | 3000000   | Tablets |                    |              |           |
| Air Pressure Low Limit :           |        | 0.400     | MPa     |                    |              |           |
| Oil Lubrication :                  |        |           |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 80        | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 30        | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |        | 60.0      | Sec     |                    |              |           |
| Initial Reject Time :              |        | 2         | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 1.00      | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 1.00      | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.00      | kN      |                    |              |           |
|                                    |        |           |         | Stop Condition ;   |              |           |
| HSP :                              | 25.0 % | 23.01     | kN      | No                 |              |           |
| HEP :                              | 20.0 % | 22.09     | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 18.78     | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 18.41     | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 18.04     | kN      | Yes 15             | Times        |           |
| LEP :                              | 20.0 % | 14.73     | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 25.0 % | 13.81     | kN      | No                 |              |           |
| SD limit :                         | 45.0 % |           |         | Yes                |              |           |
| Pre HSP                            |        | 40.00     | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | N      |           |         |                    |              |           |

### Pressure Data

|                      |            |    |       |            |    |            |    |
|----------------------|------------|----|-------|------------|----|------------|----|
| Mean Pre Pressure :  | 1.97       | kN | Min : | 1.92       | kN | Punch NO.; | 3  |
| SD :                 | 1.10       | %  | Max : | 2.03       | kN | Punch NO.; | 40 |
| Mean Main Pressure : | 18.49      | kN | Min : | 17.10      | kN | Punch NO.; | 18 |
| SD :                 | 3.30       | %  | Max : | 20.41      | kN | Punch NO.; | 57 |
| Filling Depth :      | Increase ; | 8  | Times | Decrease ; | 10 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 258720   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 14       | RPM          |
| Pre Upper Punch Position ;    | 3.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 7.00    | mm  | Pre Thickness ;  | 4.00     | mm           |
| Main Upper Punch Position ;   | 3.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.70    | mm  | Main Thickness ; | 2.70     | mm           |
| Filling Depth :               | 7.88    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.830   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 11      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 22      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.49 | kN |             |    |
|                  | Max ;     | 0.67 | kN | Max Punch ; | 30 |
| Lower Punch :    | Average ; | 0.18 | kN |             |    |
|                  | Max ;     | 0.29 | kN | Max Punch ; | 39 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                   |         |       |            |         |
|-----------------|-------------------|---------|-------|------------|---------|
| Total Counter : | 250208            | Tablets |       |            |         |
| A.W.C Counter : | 246274            | Tablets |       |            |         |
| HEP :           | 26 (0.0%)         | Tablets | LEP : | 482 (0.2%) | Tablets |
| GOOD :          | 245766<br>(99.8%) | Tablets |       |            |         |