

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | SERTRA100MG<br>STSH4B00 |
| User ID :        | pb97604       | Batch NO. :          | SHM2503810              |
| Print Interval : | 50000 Tablets | Running Time :       | 01 Hour 56 Min 00 Sec   |
| Total Counter :  | 500478        | Total Running Time : | 2408 Hour 31 Min        |
| Station :        | Station 1     |                      |                         |

### Setting Value

|                                    |             |                   |         |                    |              |           |
|------------------------------------|-------------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 58                | %       | Manual ;           | 20           | RPM       |
| Filling Cam :                      |             | Cam C<br>8.5-14mm |         | Cam Range :        | Min :        | 6.50 mm   |
| Target Quantity :                  |             | 3000000           | Tablets |                    | Max :        | 12.00 mm  |
| Air Pressure Low Limit :           |             | 0.400             | MPa     |                    |              |           |
| Oil Lubrication :                  |             |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 80                | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 30                | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |             | 60.0              | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 1.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 1.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.00              | kN      |                    |              |           |
|                                    |             |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 25.0 %      | 23.31             | kN      | No                 |              |           |
| HEP :                              | 20.0 %      | 22.38             | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %       | 19.02             | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 18.65             | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 18.28             | kN      | Yes 15             | Times        |           |
| LEP :                              | 20.0 %      | 14.92             | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 25.0 %      | 13.99             | kN      | No                 |              |           |
| SD limit :                         | 45.0 %      |                   |         | Yes                |              |           |
| Pre HSP                            |             | 40.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |                   |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | None        |                   |         |                    |              |           |

### Pressure Data

|                      |              |       |               |       |    |            |    |
|----------------------|--------------|-------|---------------|-------|----|------------|----|
| Mean Pre Pressure :  | 1.76         | kN    | Min :         | 1.66  | kN | Punch NO.; | 60 |
| SD :                 | 1.50         | %     | Max :         | 1.81  | kN | Punch NO.; | 38 |
| Mean Main Pressure : | 18.88        | kN    | Min :         | 16.02 | kN | Punch NO.; | 63 |
| SD :                 | 4.00         | %     | Max :         | 20.31 | kN | Punch NO.; | 75 |
| Filling Depth :      | Increase ; 6 | Times | Decrease ; 10 | Times |    |            |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 258720   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 16       | RPM          |
| Pre Upper Punch Position ;    | 3.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 7.00    | mm  | Pre Thickness ;  | 4.00     | mm           |
| Main Upper Punch Position ;   | 3.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.51    | mm  | Main Thickness ; | 2.51     | mm           |
| Filling Depth :               | 7.98    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.817   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 34      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 25      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.58 | kN |             |    |
|                  | Max ;     | 0.79 | kN | Max Punch ; | 28 |
| Lower Punch :    | Average ; | 0.19 | kN |             |    |
|                  | Max ;     | 0.28 | kN | Max Punch ; | 39 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                   |         |       |            |         |
|-----------------|-------------------|---------|-------|------------|---------|
| Total Counter : | 500478            | Tablets |       |            |         |
| A.W.C Counter : | 496416            | Tablets |       |            |         |
| HEP :           | 26 (0.0%)         | Tablets | LEP : | 489 (0.1%) | Tablets |
| GOOD :          | 495901<br>(99.9%) | Tablets |       |            |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | SERTRA100MG<br>STSH4B00 |
| User ID :        | pb97604       | Batch NO. :          | SHM2503810              |
| Print Interval : | 50000 Tablets | Running Time :       | 01 Hour 56 Min 00 Sec   |
| Total Counter :  | 500478        | Total Running Time : | 2408 Hour 31 Min        |
| Station :        | Station 2     |                      |                         |

### Setting Value

|                                    |        |           |         |                    |              |           |
|------------------------------------|--------|-----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 50        | %       | Manual ;           | 21           | RPM       |
| Filling Cam :                      |        | Cam C     |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |        | 8.5-14mm  |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |        | 3000000   | Tablets |                    |              |           |
| Air Pressure Low Limit :           |        | 0.400     | MPa     |                    |              |           |
| Oil Lubrication :                  |        |           |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 80        | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 30        | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |        | 60.0      | Sec     |                    |              |           |
| Initial Reject Time :              |        | 2         | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 1.00      | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 1.00      | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.00      | kN      |                    |              |           |
|                                    |        |           |         | Stop Condition ;   |              |           |
| HSP :                              | 25.0 % | 24.36     | kN      | No                 |              |           |
| HEP :                              | 20.0 % | 23.39     | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 19.88     | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 19.49     | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 19.10     | kN      | Yes 15             | Times        |           |
| LEP :                              | 20.0 % | 15.59     | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 25.0 % | 14.62     | kN      | No                 |              |           |
| SD limit :                         | 45.0 % |           |         | Yes                |              |           |
| Pre HSP                            |        | 40.00     | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | N      |           |         |                    |              |           |

### Pressure Data

|                      |            |    |       |            |    |            |    |
|----------------------|------------|----|-------|------------|----|------------|----|
| Mean Pre Pressure :  | 1.94       | kN | Min : | 1.89       | kN | Punch NO.; | 21 |
| SD :                 | 1.10       | %  | Max : | 2.00       | kN | Punch NO.; | 32 |
| Mean Main Pressure : | 19.61      | kN | Min : | 17.91      | kN | Punch NO.; | 18 |
| SD :                 | 3.00       | %  | Max : | 20.91      | kN | Punch NO.; | 57 |
| Filling Depth :      | Increase ; | 8  | Times | Decrease ; | 16 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 258720   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 14       | RPM          |
| Pre Upper Punch Position ;    | 3.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 7.00    | mm  | Pre Thickness ;  | 4.00     | mm           |
| Main Upper Punch Position ;   | 3.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.67    | mm  | Main Thickness ; | 2.67     | mm           |
| Filling Depth :               | 7.85    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.817   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 34      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 25      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.58 | kN |             |    |
|                  | Max ;     | 0.79 | kN | Max Punch ; | 28 |
| Lower Punch :    | Average ; | 0.19 | kN |             |    |
|                  | Max ;     | 0.28 | kN | Max Punch ; | 39 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                   |         |       |            |         |
|-----------------|-------------------|---------|-------|------------|---------|
| Total Counter : | 500478            | Tablets |       |            |         |
| A.W.C Counter : | 496416            | Tablets |       |            |         |
| HEP :           | 26 (0.0%)         | Tablets | LEP : | 489 (0.1%) | Tablets |
| GOOD :          | 495901<br>(99.9%) | Tablets |       |            |         |