

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	cb83530	Batch NO. :	SHM2503810
Print Interval :	50000 Tablets	Running Time :	06 Hour 23 Min 29 Sec
Total Counter :	1651278	Total Running Time :	2412 Hour 59 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	58	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	23.81	kN	No		
HEP :	20.0 %	22.86	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	19.43	kN	Yes 15	Times	
Ref :		19.05	kN			
LCP :	2.0 %	18.67	kN	Yes 15	Times	
LEP :	20.0 %	15.24	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	14.29	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.71	kN	Min :	1.66	kN	Punch NO.;	63
SD :	0.80	%	Max :	1.74	kN	Punch NO.;	26
Mean Main Pressure :	19.00	kN	Min :	17.66	kN	Punch NO.;	63
SD :	2.30	%	Max :	20.18	kN	Punch NO.;	40
Filling Depth :	Increase ; 14	Times	Decrease ; 34	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.51	mm	Main Thickness ;	2.51	mm
Filling Depth :	8.00	mm	Current Cam :	Cam C	
Main Air pressure :	0.820	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	29	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.51	kN		
	Max ;	0.61	kN	Max Punch ;	68
Lower Punch :	Average ;	0.18	kN		
	Max ;	0.25	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1651278	Tablets			
A.W.C Counter :	1646878	Tablets			
HEP :	44 (0.0%)	Tablets	LEP :	1057 (0.1%)	Tablets
GOOD :	1645777 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	cb83530	Batch NO. :	SHM2503810
Print Interval :	50000 Tablets	Running Time :	06 Hour 23 Min 29 Sec
Total Counter :	1651278	Total Running Time :	2412 Hour 59 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	56	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	27.51	kN	No		
HEP :	20.0 %	26.41	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	22.45	kN	Yes 15	Times	
Ref :		22.01	kN			
LCP :	2.0 %	21.57	kN	Yes 15	Times	
LEP :	20.0 %	17.61	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	16.50	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.92	kN	Min :	1.85	kN	Punch NO.;	8
SD :	1.20	%	Max :	1.98	kN	Punch NO.;	72
Mean Main Pressure :	21.74	kN	Min :	19.14	kN	Punch NO.;	8
SD :	3.40	%	Max :	23.97	kN	Punch NO.;	5
Filling Depth :	Increase ;	10	Times	Decrease ;	61	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.67	mm	Main Thickness ;	2.67	mm
Filling Depth :	7.82	mm	Current Cam :	Cam C	
Main Air pressure :	0.820	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	29	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.51	kN		
	Max ;	0.61	kN	Max Punch ;	68
Lower Punch :	Average ;	0.18	kN		
	Max ;	0.25	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1651278	Tablets			
A.W.C Counter :	1646878	Tablets			
HEP :	44 (0.0%)	Tablets	LEP :	1057 (0.1%)	Tablets
GOOD :	1645777 (99.9%)	Tablets			