

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	rp98927	Batch NO. :	SHM2503810
Print Interval :	50000 Tablets	Running Time :	11 Hour 25 Min 38 Sec
Total Counter :	2952310	Total Running Time :	2418 Hour 2 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	58	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	24.75	kN	No		
HEP :	20.0 %	23.76	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	20.20	kN	Yes 15	Times	
Ref :		19.80	kN			
LCP :	2.0 %	19.40	kN	Yes 15	Times	
LEP :	20.0 %	15.84	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	14.85	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.70	kN	Min :	1.60	kN	Punch NO.;	8
SD :	1.10	%	Max :	1.74	kN	Punch NO.;	67
Mean Main Pressure :	19.75	kN	Min :	17.10	kN	Punch NO.;	8
SD :	2.90	%	Max :	21.08	kN	Punch NO.;	60
Filling Depth :	Increase ; 18	Times	Decrease ;	45	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.51	mm	Main Thickness ;	2.51	mm
Filling Depth :	8.02	mm	Current Cam :	Cam C	
Main Air pressure :	0.813	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	27	Min			
Lower Punch Remain Time (S2):	28	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.44	kN		
	Max ;	0.56	kN	Max Punch ;	67
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.26	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2952310	Tablets			
A.W.C Counter :	2947711	Tablets			
HEP :	51 (0.0%)	Tablets	LEP :	1105 (0.0%)	Tablets
GOOD :	2946555 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	rp98927	Batch NO. :	SHM2503810
Print Interval :	50000 Tablets	Running Time :	11 Hour 25 Min 38 Sec
Total Counter :	2952310	Total Running Time :	2418 Hour 2 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	56	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	26.54	kN	No		
HEP :	20.0 %	25.47	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	21.65	kN	Yes	15	Times
Ref :		21.23	kN			
LCP :	2.0 %	20.80	kN	Yes	15	Times
LEP :	20.0 %	16.98	kN	Yes	10	Rotations 15 Tablets
LSP :	25.0 %	15.92	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.91	kN	Min :	1.87	kN	Punch NO.;	22
SD :	1.10	%	Max :	1.96	kN	Punch NO.;	9
Mean Main Pressure :	20.88	kN	Min :	19.35	kN	Punch NO.;	29
SD :	3.40	%	Max :	22.50	kN	Punch NO.;	60
Filling Depth :	Increase ;	15	Times	Decrease ;	97	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.75	mm	Main Thickness ;	2.75	mm
Filling Depth :	7.95	mm	Current Cam :	Cam C	
Main Air pressure :	0.813	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	27	Min			
Lower Punch Remain Time (S2):	28	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.44	kN		
	Max ;	0.56	kN	Max Punch ;	67
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.26	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2952310	Tablets			
A.W.C Counter :	2947711	Tablets			
HEP :	51 (0.0%)	Tablets	LEP :	1105 (0.0%)	Tablets
GOOD :	2946555 (100.0%)	Tablets			