

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	pb97604	Batch NO. :	SHM2503910
Print Interval :	50000 Tablets	Running Time :	09 Hour 41 Min 05 Sec
Total Counter :	2501812	Total Running Time :	2427 Hour 44 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	62	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	24.96	kN	No		
HEP :	20.0 %	23.97	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	20.37	kN	Yes 15	Times	
Ref :		19.97	kN			
LCP :	2.0 %	19.57	kN	Yes 15	Times	
LEP :	20.0 %	15.98	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	14.98	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.77	kN	Min :	1.69	kN	Punch NO.;	57
		1.10	%	Max :	1.82	kN	Punch NO.;	10
Mean Main Pressure :	SD :	20.22	kN	Min :	18.19	kN	Punch NO.;	57
		2.70	%	Max :	21.49	kN	Punch NO.;	40
Filling Depth :	Increase ;	36	Times	Decrease ;	65	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	17	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.90	mm	Pre Thickness ;	3.90	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.55	mm	Main Thickness ;	2.55	mm
Filling Depth :	8.20	mm	Current Cam :	Cam C	
Main Air pressure :	0.820	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.61	kN		
	Max ;	0.83	kN	Max Punch ;	67
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.20	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2501812	Tablets			
A.W.C Counter :	2498109	Tablets			
HEP :	31 (0.0%)	Tablets	LEP :	14 (0.0%)	Tablets
GOOD :	2498064 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	pb97604	Batch NO. :	SHM2503910
Print Interval :	50000 Tablets	Running Time :	09 Hour 41 Min 05 Sec
Total Counter :	2501812	Total Running Time :	2427 Hour 44 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	56	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	24.74	kN	No		
HEP :	20.0 %	23.75	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	20.18	kN	Yes 15	Times	
Ref :		19.79	kN			
LCP :	2.0 %	19.39	kN	Yes 15	Times	
LEP :	20.0 %	15.83	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	14.84	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.92	kN	Min :	1.89	kN	Punch NO.;	56
SD :	1.00	%	Max :	1.99	kN	Punch NO.;	60
Mean Main Pressure :	19.88	kN	Min :	18.47	kN	Punch NO.;	48
SD :	4.10	%	Max :	22.13	kN	Punch NO.;	60
Filling Depth :	Increase ;	28	Times	Decrease ;	113	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.78	mm	Main Thickness ;	2.78	mm
Filling Depth :	8.17	mm	Current Cam :	Cam C	
Main Air pressure :	0.820	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.61	kN		
	Max ;	0.82	kN	Max Punch ;	67
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.20	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2501812	Tablets			
A.W.C Counter :	2498186	Tablets			
HEP :	31 (0.0%)	Tablets	LEP :	14 (0.0%)	Tablets
GOOD :	2498141	Tablets			
	(100.0%)				