

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	sj97904	Batch NO. :	SHM2504010
Print Interval :	50000 Tablets	Running Time :	07 Hour 10 Min 04 Sec
Total Counter :	1851624	Total Running Time :	2436 Hour 42 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	58	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	24.14	kN	No		
HEP :	20.0 %	23.17	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	19.70	kN	Yes 15	Times	
Ref :		19.31	kN			
LCP :	2.0 %	18.92	kN	Yes 15	Times	
LEP :	20.0 %	15.45	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	14.48	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.65	kN	Min :	1.54	kN	Punch NO.;	61
		1.30	%	Max :	1.71	kN	Punch NO.;	70
Mean Main Pressure :	SD :	19.30	kN	Min :	16.34	kN	Punch NO.;	61
		3.10	%	Max :	20.55	kN	Punch NO.;	67
Filling Depth :	Increase ;	64	Times	Decrease ;	84	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.90	mm	Pre Thickness ;	3.90	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.55	mm	Main Thickness ;	2.55	mm
Filling Depth :	8.22	mm	Current Cam :	Cam C	
Main Air pressure :	0.824	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	31	Min			
Lower Punch Remain Time (S2):	22	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.70	kN		
	Max ;	0.85	kN	Max Punch ;	66
Lower Punch :	Average ;	0.18	kN		
	Max ;	0.23	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1851624	Tablets			
A.W.C Counter :	1846474	Tablets			
HEP :	5 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1846469 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	sj97904	Batch NO. :	SHM2504010
Print Interval :	50000 Tablets	Running Time :	07 Hour 10 Min 04 Sec
Total Counter :	1851624	Total Running Time :	2436 Hour 42 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	57	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	24.13	kN	No		
HEP :	20.0 %	23.16	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	19.69	kN	Yes 15	Times	
Ref :		19.30	kN			
LCP :	2.0 %	18.92	kN	Yes 15	Times	
LEP :	20.0 %	15.44	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	14.48	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.80	kN	Min :	1.76	kN	Punch NO.;	1
SD :	1.00	%	Max :	1.86	kN	Punch NO.;	67
Mean Main Pressure :	19.27	kN	Min :	17.11	kN	Punch NO.;	18
SD :	4.00	%	Max :	21.22	kN	Punch NO.;	60
Filling Depth :	Increase ;	41	Times	Decrease ;	131	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.78	mm	Main Thickness ;	2.78	mm
Filling Depth :	7.82	mm	Current Cam :	Cam C	
Main Air pressure :	0.824	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	31	Min			
Lower Punch Remain Time (S2):	22	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.70	kN		
	Max ;	0.85	kN	Max Punch ;	66
Lower Punch :	Average ;	0.18	kN		
	Max ;	0.23	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1851624	Tablets			
A.W.C Counter :	1846474	Tablets			
HEP :	5 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1846469 (100.0%)	Tablets			