

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	pb97604	Batch NO. :	SHM2504110
Print Interval :	50000 Tablets	Running Time :	01 Hour 13 Min 50 Sec
Total Counter :	317588	Total Running Time :	2442 Hour 16 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	65	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	23.64	kN	No		
HEP :	20.0 %	22.70	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	19.29	kN	Yes 15	Times	
Ref :		18.91	kN			
LCP :	2.0 %	18.54	kN	Yes 15	Times	
LEP :	20.0 %	15.13	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	14.19	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.74	kN	Min :	1.71	kN	Punch NO.;	19
SD :	1.00	%	Max :	1.80	kN	Punch NO.;	10
Mean Main Pressure :	18.94	kN	Min :	17.78	kN	Punch NO.;	63
SD :	2.40	%	Max :	20.16	kN	Punch NO.;	60
Filling Depth :	Increase ; 13	Times	Decrease ; 10	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.80	mm	Pre Thickness ;	3.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.53	mm	Main Thickness ;	2.54	mm
Filling Depth :	7.72	mm	Current Cam :	Cam C	
Main Air pressure :	0.821	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	33	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	1.08	kN		
	Max ;	1.41	kN	Max Punch ;	26
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.22	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	317588	Tablets			
A.W.C Counter :	311098	Tablets			
HEP :	46 (0.0%)	Tablets	LEP :	264 (0.1%)	Tablets
GOOD :	310788 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	pb97604	Batch NO. :	SHM2504110
Print Interval :	50000 Tablets	Running Time :	01 Hour 13 Min 50 Sec
Total Counter :	317588	Total Running Time :	2442 Hour 16 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	66	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	23.72	kN	No		
HEP :	20.0 %	22.77	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	19.36	kN	Yes 15	Times	
Ref :		18.98	kN			
LCP :	2.0 %	18.60	kN	Yes 15	Times	
LEP :	20.0 %	15.18	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	14.23	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.85	kN	Min :	1.83	kN	Punch NO.;	25
SD :	0.90	%	Max :	1.90	kN	Punch NO.;	62
Mean Main Pressure :	19.14	kN	Min :	18.04	kN	Punch NO.;	11
SD :	3.20	%	Max :	21.24	kN	Punch NO.;	57
Filling Depth :	Increase ;	14	Times	Decrease ;	18	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.78	mm	Main Thickness ;	2.79	mm
Filling Depth :	7.72	mm	Current Cam :	Cam C	
Main Air pressure :	0.821	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	33	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	1.08	kN		
	Max ;	1.41	kN	Max Punch ;	26
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.22	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	317588	Tablets			
A.W.C Counter :	311098	Tablets			
HEP :	46 (0.0%)	Tablets	LEP :	264 (0.1%)	Tablets
GOOD :	310788 (99.9%)	Tablets			