

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	sj97904	Batch NO. :	SHM2504110
Print Interval :	50000 Tablets	Running Time :	11 Hour 30 Min 15 Sec
Total Counter :	2969366	Total Running Time :	2452 Hour 33 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	65	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	24.64	kN	No		
HEP :	20.0 %	23.65	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	20.11	kN	Yes 15	Times	
Ref :		19.71	kN			
LCP :	2.0 %	19.32	kN	Yes 15	Times	
LEP :	20.0 %	15.77	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	14.78	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.66	kN	Min :	1.60	kN	Punch NO.;	47
		1.50	%	Max :	1.72	kN	Punch NO.;	57
Mean Main Pressure :	SD :	19.64	kN	Min :	18.46	kN	Punch NO.;	27
		3.10	%	Max :	21.45	kN	Punch NO.;	57
Filling Depth :	Increase ;	33	Times	Decrease ;	56	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.80	mm	Pre Thickness ;	3.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.53	mm	Main Thickness ;	2.54	mm
Filling Depth :	7.78	mm	Current Cam :	Cam C	
Main Air pressure :	0.806	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.67	kN		
	Max ;	0.83	kN	Max Punch ;	57
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.21	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2969366	Tablets			
A.W.C Counter :	2961536	Tablets			
HEP :	138 (0.0%)	Tablets	LEP :	266 (0.0%)	Tablets
GOOD :	2961132 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	sj97904	Batch NO. :	SHM2504110
Print Interval :	50000 Tablets	Running Time :	11 Hour 30 Min 15 Sec
Total Counter :	2969366	Total Running Time :	2452 Hour 33 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	66	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	25.82	kN	No		
HEP :	20.0 %	24.79	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	21.07	kN	Yes 15	Times	
Ref :		20.66	kN			
LCP :	2.0 %	20.24	kN	Yes 15	Times	
LEP :	20.0 %	16.53	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	15.49	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.80	kN	Min :	1.75	kN	Punch NO.;	13
SD :	1.10	%	Max :	1.85	kN	Punch NO.;	58
Mean Main Pressure :	20.94	kN	Min :	19.58	kN	Punch NO.;	25
SD :	3.90	%	Max :	23.40	kN	Punch NO.;	57
Filling Depth :	Increase ;	32	Times	Decrease ;	48	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.78	mm	Main Thickness ;	2.79	mm
Filling Depth :	7.79	mm	Current Cam :	Cam C	
Main Air pressure :	0.806	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.67	kN		
	Max ;	0.85	kN	Max Punch ;	57
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.21	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2969366	Tablets			
A.W.C Counter :	2961613	Tablets			
HEP :	138 (0.0%)	Tablets	LEP :	266 (0.0%)	Tablets
GOOD :	2961209 (100.0%)	Tablets			