

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	yu98249	Batch NO. :	MRM2502750
Print Interval :	50000 Tablets	Running Time :	02 Hour 53 Min 54 Sec
Total Counter :	386662	Total Running Time :	2455 Hour 31 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	70	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	15.29	kN	No		
HEP :	20.0 %	14.68	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.48	kN	Yes 15	Times	
Ref :		12.23	kN			
LCP :	2.0 %	11.99	kN	Yes 15	Times	
LEP :	20.0 %	9.79	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	9.18	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.16	kN	Min :	1.91	kN	Punch NO.;	18
SD :	6.10	%	Max :	2.60	kN	Punch NO.;	25
Mean Main Pressure :	12.43	kN	Min :	11.98	kN	Punch NO.;	32
SD :	1.70	%	Max :	13.08	kN	Punch NO.;	24
Filling Depth :	Increase ; 4	Times	Decrease ;	18	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.00	mm	Main Thickness ;	3.00	mm
Filling Depth :	7.86	mm	Current Cam :	Cam C	
Main Air pressure :	0.837	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.04	kN	Max Punch ;	29
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.18	kN	Max Punch ;	39
Ejection Force :	Average ;	1.39	kN		
	Max ;	1.42	kN	Max Punch ;	4

Tablet Data (N/A)

Total Counter :	386662	Tablets			
A.W.C Counter :	369960	Tablets			
HEP :	9 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	369951 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	yu98249	Batch NO. :	MRM2502750
Print Interval :	50000 Tablets	Running Time :	02 Hour 53 Min 54 Sec
Total Counter :	386662	Total Running Time :	2455 Hour 31 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	78	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	16.63	kN	No		
HEP :	20.0 %	15.96	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.57	kN	Yes 15	Times	
Ref :		13.30	kN			
LCP :	2.0 %	13.03	kN	Yes 15	Times	
LEP :	20.0 %	10.64	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	9.98	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.12	kN	Min :	1.87	kN	Punch NO.;	20
SD :	4.50	%	Max :	2.34	kN	Punch NO.;	49
Mean Main Pressure :	13.40	kN	Min :	12.52	kN	Punch NO.;	42
SD :	2.70	%	Max :	14.13	kN	Punch NO.;	53
Filling Depth :	Increase ;	25	Times	Decrease ;	28	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.10	mm	Main Thickness ;	3.10	mm
Filling Depth :	7.85	mm	Current Cam :	Cam C	
Main Air pressure :	0.837	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.04	kN	Max Punch ;	29
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.18	kN	Max Punch ;	39
Ejection Force :	Average ;	1.39	kN		
	Max ;	1.43	kN	Max Punch ;	11

Tablet Data (N/A)

Total Counter :	386662	Tablets			
A.W.C Counter :	369960	Tablets			
HEP :	9 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	369951 (100.0%)	Tablets			