

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	pb97604	Batch NO. :	MRM2502750
Print Interval :	50000 Tablets	Running Time :	06 Hour 09 Min 02 Sec
Total Counter :	800246	Total Running Time :	2458 Hour 46 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	15.91	kN	No		
HEP :	20.0 %	15.27	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.98	kN	Yes 15	Times	
Ref :		12.73	kN			
LCP :	2.0 %	12.47	kN	Yes 15	Times	
LEP :	20.0 %	10.18	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	9.55	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.33	kN	Min :	2.12	kN	Punch NO.;	9
SD :	4.90	%	Max :	2.65	kN	Punch NO.;	36
Mean Main Pressure :	12.79	kN	Min :	12.28	kN	Punch NO.;	6
SD :	2.00	%	Max :	13.46	kN	Punch NO.;	53
Filling Depth :	Increase ; 8	Times	Decrease ; 27	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.00	mm	Main Thickness ;	3.00	mm
Filling Depth :	7.95	mm	Current Cam :	Cam C	
Main Air pressure :	0.726	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.04	kN	Max Punch ;	35
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.13	kN	Max Punch ;	27
Ejection Force :	Average ;	1.27	kN		
	Max ;	1.30	kN	Max Punch ;	18

Tablet Data (N/A)

Total Counter :	800246	Tablets			
A.W.C Counter :	781566	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	781556 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	pb97604	Batch NO. :	MRM2502750
Print Interval :	50000 Tablets	Running Time :	06 Hour 09 Min 02 Sec
Total Counter :	800246	Total Running Time :	2458 Hour 46 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	74	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	16.63	kN	No		
HEP :	20.0 %	15.96	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.57	kN	Yes 15	Times	
Ref :		13.30	kN			
LCP :	2.0 %	13.03	kN	Yes 15	Times	
LEP :	20.0 %	10.64	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	9.98	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.08	kN	Min :	1.87	kN	Punch NO.;	19
		5.10	%	Max :	2.35	kN	Punch NO.;	37
Mean Main Pressure :	SD :	13.30	kN	Min :	12.61	kN	Punch NO.;	31
		2.50	%	Max :	13.97	kN	Punch NO.;	50
Filling Depth :	Increase ;	42	Times	Decrease ;	47	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.10	mm	Main Thickness ;	3.10	mm
Filling Depth :	7.83	mm	Current Cam :	Cam C	
Main Air pressure :	0.726	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.03	kN	Max Punch ;	35
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.13	kN	Max Punch ;	27
Ejection Force :	Average ;	1.27	kN		
	Max ;	1.30	kN	Max Punch ;	18

Tablet Data (N/A)

Total Counter :	800246	Tablets			
A.W.C Counter :	781566	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	781556 (100.0%)	Tablets			