

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	rp98927	Batch NO. :	MRM2502750
Print Interval :	50000 Tablets	Running Time :	08 Hour 00 Min 39 Sec
Total Counter :	4094732	Total Running Time :	2484 Hour 42 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	92	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	15.76	kN	No		
HEP :	20.0 %	15.13	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.86	kN	Yes 15	Times	
Ref :		12.61	kN			
LCP :	2.0 %	12.36	kN	Yes 15	Times	
LEP :	20.0 %	10.09	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	9.46	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.39	kN	Min :	2.08	kN	Punch NO.;	18
SD :	5.80	%	Max :	2.83	kN	Punch NO.;	53
Mean Main Pressure :	12.68	kN	Min :	12.42	kN	Punch NO.;	31
SD :	1.60	%	Max :	13.52	kN	Punch NO.;	13
Filling Depth :	Increase ; 50	Times	Decrease ; 27	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.00	mm	Main Thickness ;	3.00	mm
Filling Depth :	7.85	mm	Current Cam :	Cam C	
Main Air pressure :	0.822	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.08	kN	Max Punch ;	29
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.16	kN	Max Punch ;	5
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	44

Tablet Data (N/A)

Total Counter :	4094732	Tablets			
A.W.C Counter :	4075711	Tablets			
HEP :	17 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	4075693 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	rp98927	Batch NO. :	MRM2502750
Print Interval :	50000 Tablets	Running Time :	08 Hour 00 Min 39 Sec
Total Counter :	4094732	Total Running Time :	2484 Hour 42 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	91	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	16.43	kN	No		
HEP :	20.0 %	15.78	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.41	kN	Yes 15	Times	
Ref :		13.15	kN			
LCP :	2.0 %	12.88	kN	Yes 15	Times	
LEP :	20.0 %	10.52	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	9.86	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.17	kN	Min :	1.97	kN	Punch NO.;	23
SD :	5.30	%	Max :	2.53	kN	Punch NO.;	37
Mean Main Pressure :	13.08	kN	Min :	12.56	kN	Punch NO.;	5
SD :	2.00	%	Max :	13.70	kN	Punch NO.;	50
Filling Depth :	Increase ;	89	Times	Decrease ;	109	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.16	mm	Main Thickness ;	3.17	mm
Filling Depth :	7.80	mm	Current Cam :	Cam C	
Main Air pressure :	0.822	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.08	kN	Max Punch ;	35
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.16	kN	Max Punch ;	5
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	44

Tablet Data (N/A)

Total Counter :	4094732	Tablets			
A.W.C Counter :	4075711	Tablets			
HEP :	17 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	4075693 (100.0%)	Tablets			