

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	rp98927	Batch NO. :	MRM2502750
Print Interval :	50000 Tablets	Running Time :	10 Hour 45 Min 37 Sec
Total Counter :	4444842	Total Running Time :	2487 Hour 27 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	92	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	15.76	kN	No		
HEP :	20.0 %	15.13	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.86	kN	Yes 15	Times	
Ref :		12.61	kN			
LCP :	2.0 %	12.36	kN	Yes 15	Times	
LEP :	20.0 %	10.09	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	9.46	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.27	kN	Min :	1.97	kN	Punch NO.;	19
		6.30	%	Max :	2.75	kN	Punch NO.;	53
Mean Main Pressure :	SD :	12.56	kN	Min :	12.23	kN	Punch NO.;	43
		1.50	%	Max :	13.24	kN	Punch NO.;	13
Filling Depth :	Increase ;	50	Times	Decrease ;	31	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.00	mm	Main Thickness ;	3.00	mm
Filling Depth :	7.87	mm	Current Cam :	Cam C	
Main Air pressure :	0.815	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.09	kN	Max Punch ;	29
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.18	kN	Max Punch ;	53
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.07	kN	Max Punch ;	31

Tablet Data (N/A)

Total Counter :	4444842	Tablets			
A.W.C Counter :	4425712	Tablets			
HEP :	17 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	4425694 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	rp98927	Batch NO. :	MRM2502750
Print Interval :	50000 Tablets	Running Time :	10 Hour 45 Min 37 Sec
Total Counter :	4444842	Total Running Time :	2487 Hour 27 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	91	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	16.83	kN	No		
HEP :	20.0 %	16.16	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.73	kN	Yes 15	Times	
Ref :		13.46	kN			
LCP :	2.0 %	13.20	kN	Yes 15	Times	
LEP :	20.0 %	10.77	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	10.10	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.33	kN	Min :	2.04	kN	Punch NO.;	27
		5.10	%	Max :	2.70	kN	Punch NO.;	53
Mean Main Pressure :	SD :	13.34	kN	Min :	12.60	kN	Punch NO.;	16
		3.10	%	Max :	14.38	kN	Punch NO.;	13
Filling Depth :	Increase ;	103	Times	Decrease ;	124	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.16	mm	Main Thickness ;	3.17	mm
Filling Depth :	7.95	mm	Current Cam :	Cam C	
Main Air pressure :	0.815	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.08	kN	Max Punch ;	29
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.18	kN	Max Punch ;	53
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.07	kN	Max Punch ;	31

Tablet Data (N/A)

Total Counter :	4444842	Tablets			
A.W.C Counter :	4425712	Tablets			
HEP :	17 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	4425694 (100.0%)	Tablets			