

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	pm98770	Batch NO. :	MRM2502850
Print Interval :	50000 Tablets	Running Time :	05 Hour 16 Min 33 Sec
Total Counter :	900420	Total Running Time :	2492 Hour 58 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	16.56	kN	No		
HEP :	20.0 %	15.90	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.51	kN	Yes 15	Times	
Ref :		13.25	kN			
LCP :	2.0 %	12.98	kN	Yes 15	Times	
LEP :	20.0 %	10.60	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	9.94	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.54	kN	Min :	3.19	kN	Punch NO.;	5
SD :	4.90	%	Max :	3.92	kN	Punch NO.;	25
Mean Main Pressure :	13.27	kN	Min :	12.85	kN	Punch NO.;	32
SD :	1.60	%	Max :	13.76	kN	Punch NO.;	35
Filling Depth :	Increase ; 82	Times	Decrease ; 36	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.61	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.90	mm	Main Thickness ;	2.90	mm
Filling Depth :	8.36	mm	Current Cam :	Cam C	
Main Air pressure :	0.658	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.06	kN	Max Punch ;	37
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.24	kN	Max Punch ;	39
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	18

Tablet Data (N/A)

Total Counter :	900420	Tablets			
A.W.C Counter :	893968	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	893958 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	pm98770	Batch NO. :	MRM2502850
Print Interval :	50000 Tablets	Running Time :	05 Hour 16 Min 33 Sec
Total Counter :	900420	Total Running Time :	2492 Hour 58 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	17.13	kN	No		
HEP :	20.0 %	16.44	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.98	kN	Yes 15	Times	
Ref :		13.70	kN			
LCP :	2.0 %	13.43	kN	Yes 15	Times	
LEP :	20.0 %	10.96	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	10.28	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.27	kN	Min :	2.89	kN	Punch NO.;	15
SD :	4.20	%	Max :	3.55	kN	Punch NO.;	42
Mean Main Pressure :	13.56	kN	Min :	12.79	kN	Punch NO.;	18
SD :	2.30	%	Max :	14.25	kN	Punch NO.;	53
Filling Depth :	Increase ;	128	Times	Decrease ;	149	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.60	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.05	mm	Main Thickness ;	3.06	mm
Filling Depth :	7.94	mm	Current Cam :	Cam C	
Main Air pressure :	0.658	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.05	kN	Max Punch ;	30
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.24	kN	Max Punch ;	39
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	18

Tablet Data (N/A)

Total Counter :	900420	Tablets			
A.W.C Counter :	893968	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	893958 (100.0%)	Tablets			