

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	vy190186	Batch NO. :	MRM2502850
Print Interval :	50000 Tablets	Running Time :	16 Hour 19 Min 38 Sec
Total Counter :	2851302	Total Running Time :	2504 Hour 3 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		220	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		300	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	16.80	kN	No		
HEP :	20.0 %	16.13	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.71	kN	Yes 15	Times	
Ref :		13.44	kN			
LCP :	2.0 %	13.18	kN	Yes 15	Times	
LEP :	20.0 %	10.76	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	10.08	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.56	kN	Min :	2.19	kN	Punch NO.;	5
SD :	7.20	%	Max :	2.91	kN	Punch NO.;	2
Mean Main Pressure :	13.45	kN	Min :	12.66	kN	Punch NO.;	42
SD :	3.60	%	Max :	14.53	kN	Punch NO.;	53
Filling Depth :	Increase ;	107	Times	Decrease ;	73	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.75	mm	Pre Thickness ;	2.76	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.90	mm	Main Thickness ;	2.90	mm
Filling Depth :	7.86	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.788	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	117	Min			
Lower Punch Remain Time (S2):	219	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.05	kN	Max Punch ;	41
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.14	kN	Max Punch ;	5
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	36

Tablet Data (N/A)

Total Counter :	2851302	Tablets			
A.W.C Counter :	2842610	Tablets			
HEP :	151 (0.0%)	Tablets	LEP :	200 (0.0%)	Tablets
GOOD :	2842259 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	vy190186	Batch NO. :	MRM2502850
Print Interval :	50000 Tablets	Running Time :	16 Hour 19 Min 38 Sec
Total Counter :	2851302	Total Running Time :	2504 Hour 3 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		220	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		300	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	19.63	kN	No		
HEP :	20.0 %	18.85	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	16.02	kN	Yes 15	Times	
Ref :		15.71	kN			
LCP :	2.0 %	15.39	kN	Yes 15	Times	
LEP :	20.0 %	12.57	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	11.78	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.51	kN	Min :	2.27	kN	Punch NO.;	12
SD :	4.30	%	Max :	2.74	kN	Punch NO.;	34
Mean Main Pressure :	15.68	kN	Min :	14.37	kN	Punch NO.;	31
SD :	3.10	%	Max :	16.71	kN	Punch NO.;	53
Filling Depth :	Increase ;	243	Times	Decrease ;	244	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.75	mm	Pre Thickness ;	2.75	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.95	mm	Main Thickness ;	2.96	mm
Filling Depth :	7.91	mm	Current Cam :	Cam C	
Main Air pressure :	0.788	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	117	Min			
Lower Punch Remain Time (S2):	219	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.05	kN	Max Punch ;	41
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.13	kN	Max Punch ;	5
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	26

Tablet Data (N/A)

Total Counter :	2851302	Tablets			
A.W.C Counter :	2842610	Tablets			
HEP :	151 (0.0%)	Tablets	LEP :	200 (0.0%)	Tablets
GOOD :	2842259 (100.0%)	Tablets			