

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	sj97904	Batch NO. :	MRM2502850
Print Interval :	50000 Tablets	Running Time :	20 Hour 05 Min 50 Sec
Total Counter :	3451598	Total Running Time :	2507 Hour 49 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	88	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	17.39	kN	No		
HEP :	20.0 %	16.70	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.19	kN	Yes 15	Times	
Ref :		13.91	kN			
LCP :	2.0 %	13.64	kN	Yes 15	Times	
LEP :	20.0 %	11.13	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	10.44	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.07	kN	Min :	1.64	kN	Punch NO.;	6
SD :	7.20	%	Max :	2.42	kN	Punch NO.;	47
Mean Main Pressure :	14.05	kN	Min :	13.33	kN	Punch NO.;	28
SD :	2.80	%	Max :	15.12	kN	Punch NO.;	53
Filling Depth :	Increase ;	138	Times	Decrease ;	110	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.90	mm	Main Thickness ;	2.90	mm
Filling Depth :	8.13	mm	Current Cam :	Cam C	
Main Air pressure :	0.775	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.06	kN	Max Punch ;	43
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.20	kN	Max Punch ;	48
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.03	kN	Max Punch ;	37

Tablet Data (N/A)

Total Counter :	3451598	Tablets			
A.W.C Counter :	3441398	Tablets			
HEP :	153 (0.0%)	Tablets	LEP :	200 (0.0%)	Tablets
GOOD :	3441045 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	sj97904	Batch NO. :	MRM2502850
Print Interval :	50000 Tablets	Running Time :	20 Hour 05 Min 50 Sec
Total Counter :	3451598	Total Running Time :	2507 Hour 49 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	92	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	19.82	kN	No		
HEP :	20.0 %	19.02	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	16.17	kN	Yes 15	Times	
Ref :		15.85	kN			
LCP :	2.0 %	15.54	kN	Yes 15	Times	
LEP :	20.0 %	12.68	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	11.89	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.22	kN	Min :	1.69	kN	Punch NO.;	6
SD :	7.80	%	Max :	2.68	kN	Punch NO.;	53
Mean Main Pressure :	15.95	kN	Min :	14.62	kN	Punch NO.;	19
SD :	3.90	%	Max :	17.62	kN	Punch NO.;	13
Filling Depth :	Increase ;	298	Times	Decrease ;	307	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	23	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.95	mm	Main Thickness ;	2.96	mm
Filling Depth :	7.93	mm	Current Cam :	Cam C	
Main Air pressure :	0.775	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.06	kN	Max Punch ;	43
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.21	kN	Max Punch ;	12
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	1

Tablet Data (N/A)

Total Counter :	3451598	Tablets			
A.W.C Counter :	3441398	Tablets			
HEP :	153 (0.0%)	Tablets	LEP :	200 (0.0%)	Tablets
GOOD :	3441045 (100.0%)	Tablets			