

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	pb97604	Batch NO. :	MRM2502850
Print Interval :	50000 Tablets	Running Time :	00 Hour 10 Min 32 Sec
Total Counter :	4101900	Total Running Time :	2511 Hour 55 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	88	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		80	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	17.71	kN	No		
HEP :	20.0 %	17.00	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.45	kN	Yes 15	Times	
Ref :		14.17	kN			
LCP :	2.0 %	13.88	kN	Yes 15	Times	
LEP :	20.0 %	11.33	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	10.63	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.07	kN	Min :	1.73	kN	Punch NO.;	6
		6.40	%	Max :	2.39	kN	Punch NO.;	43
Mean Main Pressure :		14.13	kN	Min :	13.19	kN	Punch NO.;	31
	SD :	2.90	%	Max :	15.14	kN	Punch NO.;	24
Filling Depth :	Increase ;	141	Times	Decrease ;	120	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.90	mm	Main Thickness ;	2.90	mm
Filling Depth :	8.01	mm	Current Cam :	Cam C	
Main Air pressure :	0.716	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	64	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.06	kN	Max Punch ;	42
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.21	kN	Max Punch ;	46
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.03	kN	Max Punch ;	37

Tablet Data (N/A)

Total Counter :	4101900	Tablets			
A.W.C Counter :	4091708	Tablets			
HEP :	153 (0.0%)	Tablets	LEP :	200 (0.0%)	Tablets
GOOD :	4091355 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFO 500mg STMR2A00
User ID :	pb97604	Batch NO. :	MRM2502850
Print Interval :	50000 Tablets	Running Time :	00 Hour 10 Min 32 Sec
Total Counter :	4101900	Total Running Time :	2511 Hour 55 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	92	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		80	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	19.73	kN	No		
HEP :	20.0 %	18.94	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	16.10	kN	Yes 15	Times	
Ref :		15.78	kN			
LCP :	2.0 %	15.47	kN	Yes 15	Times	
LEP :	20.0 %	12.63	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	11.84	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.21	kN	Min :	1.92	kN	Punch NO.;	30
SD :	6.30	%	Max :	2.51	kN	Punch NO.;	11
Mean Main Pressure :	15.70	kN	Min :	14.67	kN	Punch NO.;	46
SD :	3.20	%	Max :	17.26	kN	Punch NO.;	14
Filling Depth :	Increase ;	314	Times	Decrease ;	325	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	23	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.97	mm	Main Thickness ;	2.98	mm
Filling Depth :	7.97	mm	Current Cam :	Cam C	
Main Air pressure :	0.716	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	64	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.06	kN	Max Punch ;	42
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.22	kN	Max Punch ;	33
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.03	kN	Max Punch ;	39

Tablet Data (N/A)

Total Counter :	4101900	Tablets			
A.W.C Counter :	4091708	Tablets			
HEP :	153 (0.0%)	Tablets	LEP :	200 (0.0%)	Tablets
GOOD :	4091355 (100.0%)	Tablets			