

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | SERTRA<br>50MG,STSH4A00 |
| User ID :        | rp98927       | Batch NO. :          | SHM2503150              |
| Print Interval : | 50000 Tablets | Running Time :       | 15 Hour 40 Min 18 Sec   |
| Total Counter :  | 4052784       | Total Running Time : | 2542 Hour 20 Min        |
| Station :        | Station 1     |                      |                         |

### Setting Value

|                                    |        |                   |         |                    |              |           |
|------------------------------------|--------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 50                | %       | Manual ;           | 20           | RPM       |
| Filling Cam :                      |        | Cam B<br>4.5-10mm |         | Cam Range :        | Min :        | 2.50 mm   |
| Target Quantity :                  |        | 6000000           | Tablets |                    | Max :        | 8.00 mm   |
| Air Pressure Low Limit :           |        | 0.400             | MPa     |                    |              |           |
| Oil Lubrication :                  |        |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 80                | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 50                | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |        | 60.0              | Sec     |                    |              |           |
| Initial Reject Time :              |        | 2                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 2.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 3.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.90              | kN      |                    |              |           |
|                                    |        |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 28.0 % | 18.63             | kN      | No                 |              |           |
| HEP :                              | 23.0 % | 17.90             | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 14.84             | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 14.55             | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 14.26             | kN      | Yes 15             | Times        |           |
| LEP :                              | 23.0 % | 11.20             | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 28.0 % | 10.48             | kN      | No                 |              |           |
| SD limit :                         | 45.0 % |                   |         | Yes                |              |           |
| Pre HSP                            |        | 40.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations         |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | None   |                   |         |                    |              |           |

### Pressure Data

|                      |            |    |       |            |     |            |    |
|----------------------|------------|----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 1.85       | kN | Min : | 1.81       | kN  | Punch NO.; | 16 |
| SD :                 | 1.00       | %  | Max : | 1.89       | kN  | Punch NO.; | 63 |
| Mean Main Pressure : | 14.23      | kN | Min : | 12.78      | kN  | Punch NO.; | 26 |
| SD :                 | 4.50       | %  | Max : | 15.73      | kN  | Punch NO.; | 73 |
| Filling Depth :      | Increase ; | 20 | Times | Decrease ; | 132 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 258720   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 14       | RPM          |
| Pre Upper Punch Position ;    | 3.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 6.00    | mm  | Pre Thickness ;  | 3.00     | mm           |
| Main Upper Punch Position ;   | 3.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.03    | mm  | Main Thickness ; | 2.03     | mm           |
| Filling Depth :               | 6.80    | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.817   | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 68      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 9       | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.29 | kN |             |    |
|                  | Max ;     | 0.42 | kN | Max Punch ; | 65 |
| Lower Punch :    | Average ; | 0.14 | kN |             |    |
|                  | Max ;     | 0.16 | kN | Max Punch ; | 31 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                     |         |       |        |         |
|-----------------|---------------------|---------|-------|--------|---------|
| Total Counter : | 4052784             | Tablets |       |        |         |
| A.W.C Counter : | 4043888             | Tablets |       |        |         |
| HEP :           | 0 (0%)              | Tablets | LEP : | 0 (0%) | Tablets |
| GOOD :          | 4043888<br>(100.0%) | Tablets |       |        |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | SERTRA<br>50MG,STSH4A00 |
| User ID :        | rp98927       | Batch NO. :          | SHM2503150              |
| Print Interval : | 50000 Tablets | Running Time :       | 15 Hour 40 Min 18 Sec   |
| Total Counter :  | 4052784       | Total Running Time : | 2542 Hour 20 Min        |
| Station :        | Station 2     |                      |                         |

### Setting Value

|                                    |        |                   |         |                    |              |           |
|------------------------------------|--------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 50                | %       | Manual ;           | 40           | RPM       |
| Filling Cam :                      |        | Cam B<br>4.5-10mm |         | Cam Range :        | Min :        | 2.50 mm   |
| Target Quantity :                  |        | 6000000           | Tablets |                    | Max :        | 8.00 mm   |
| Air Pressure Low Limit :           |        | 0.400             | MPa     |                    |              |           |
| Oil Lubrication :                  |        |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 80                | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 50                | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |        | 60.0              | Sec     |                    |              |           |
| Initial Reject Time :              |        | 2                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 2.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 3.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.90              | kN      |                    |              |           |
|                                    |        |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 28.0 % | 18.31             | kN      | No                 |              |           |
| HEP :                              | 23.0 % | 17.60             | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 14.59             | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 14.31             | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 14.02             | kN      | Yes 15             | Times        |           |
| LEP :                              | 23.0 % | 11.02             | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 28.0 % | 10.30             | kN      | No                 |              |           |
| SD limit :                         | 45.0 % |                   |         | Yes                |              |           |
| Pre HSP                            |        | 40.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations         |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | N      |                   |         |                    |              |           |

### Pressure Data

|                      |            |    |       |            |    |            |    |
|----------------------|------------|----|-------|------------|----|------------|----|
| Mean Pre Pressure :  | 1.51       | kN | Min : | 1.48       | kN | Punch NO.; | 22 |
| SD :                 | 1.10       | %  | Max : | 1.56       | kN | Punch NO.; | 9  |
| Mean Main Pressure : | 14.22      | kN | Min : | 13.32      | kN | Punch NO.; | 10 |
| SD :                 | 3.00       | %  | Max : | 15.22      | kN | Punch NO.; | 69 |
| Filling Depth :      | Increase ; | 23 | Times | Decrease ; | 46 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 258720   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 14       | RPM          |
| Pre Upper Punch Position ;    | 3.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 6.00    | mm  | Pre Thickness ;  | 3.00     | mm           |
| Main Upper Punch Position ;   | 3.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.06    | mm  | Main Thickness ; | 2.06     | mm           |
| Filling Depth :               | 6.81    | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.817   | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 68      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 9       | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.30 | kN |             |    |
|                  | Max ;     | 0.40 | kN | Max Punch ; | 47 |
| Lower Punch :    | Average ; | 0.14 | kN |             |    |
|                  | Max ;     | 0.16 | kN | Max Punch ; | 31 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                     |         |       |        |         |
|-----------------|---------------------|---------|-------|--------|---------|
| Total Counter : | 4052784             | Tablets |       |        |         |
| A.W.C Counter : | 4043965             | Tablets |       |        |         |
| HEP :           | 0 (0%)              | Tablets | LEP : | 0 (0%) | Tablets |
| GOOD :          | 4043965<br>(100.0%) | Tablets |       |        |         |