

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	pb97604	Batch NO. :	SHM2503250
Print Interval :	50000 Tablets	Running Time :	02 Hour 24 Min 18 Sec
Total Counter :	621638	Total Running Time :	2551 Hour 55 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	34	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	16.26	kN	No		
HEP :	23.0 %	15.62	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.96	kN	Yes 15	Times	
Ref :		12.70	kN			
LCP :	2.0 %	12.45	kN	Yes 15	Times	
LEP :	23.0 %	9.78	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	9.15	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.99	kN	Min :	1.95	kN	Punch NO.;	17
SD :	0.80	%	Max :	2.04	kN	Punch NO.;	60
Mean Main Pressure :	12.82	kN	Min :	11.74	kN	Punch NO.;	23
SD :	3.30	%	Max :	14.53	kN	Punch NO.;	60
Filling Depth :	Increase ;	13	Times	Decrease ;	24	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.95	mm	Main Thickness ;	1.96	mm
Filling Depth :	6.26	mm	Current Cam :	Cam B	
Main Air pressure :	0.789	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	48	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.26	kN	Max Punch ;	65
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.15	kN	Max Punch ;	74
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	621638	Tablets			
A.W.C Counter :	615640	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	615640 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	pb97604	Batch NO. :	SHM2503250
Print Interval :	50000 Tablets	Running Time :	02 Hour 24 Min 18 Sec
Total Counter :	621638	Total Running Time :	2551 Hour 55 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	35	%	Manual ;	40	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	15.79	kN	No		
HEP :	23.0 %	15.17	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.58	kN	Yes 15	Times	
Ref :		12.33	kN			
LCP :	2.0 %	12.09	kN	Yes 15	Times	
LEP :	23.0 %	9.50	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	8.88	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.74	kN	Min :	1.69	kN	Punch NO.;	26
SD :	1.40	%	Max :	1.83	kN	Punch NO.;	38
Mean Main Pressure :	12.31	kN	Min :	11.25	kN	Punch NO.;	26
SD :	3.90	%	Max :	13.56	kN	Punch NO.;	46
Filling Depth :	Increase ;	7	Times	Decrease ;	11	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.00	mm	Main Thickness ;	2.01	mm
Filling Depth :	5.99	mm	Current Cam :	Cam B	
Main Air pressure :	0.789	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	48	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.27	kN	Max Punch ;	23
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.15	kN	Max Punch ;	74
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	621638	Tablets			
A.W.C Counter :	615640	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	615640 (100.0%)	Tablets			