

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | SERTRA<br>50MG,STSH4A00 |
| User ID :        | pb97604       | Batch NO. :          | SHM2503250              |
| Print Interval : | 50000 Tablets | Running Time :       | 04 Hour 31 Min 47 Sec   |
| Total Counter :  | 1172034       | Total Running Time : | 2554 Hour 3 Min         |
| Station :        | Station 1     |                      |                         |

### Setting Value

|                                    |        |                   |         |                    |              |           |
|------------------------------------|--------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 37                | %       | Manual ;           | 20           | RPM       |
| Filling Cam :                      |        | Cam B<br>4.5-10mm |         | Cam Range :        | Min :        | 2.50 mm   |
| Target Quantity :                  |        | 6000000           | Tablets |                    | Max :        | 8.00 mm   |
| Air Pressure Low Limit :           |        | 0.400             | MPa     |                    |              |           |
| Oil Lubrication :                  |        |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 50                | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 50                | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |        | 60.0              | Sec     |                    |              |           |
| Initial Reject Time :              |        | 2                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 2.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 3.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.90              | kN      |                    |              |           |
|                                    |        |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 28.0 % | 16.08             | kN      | No                 |              |           |
| HEP :                              | 23.0 % | 15.45             | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 12.81             | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 12.56             | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 12.31             | kN      | Yes 15             | Times        |           |
| LEP :                              | 23.0 % | 9.67              | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 28.0 % | 9.04              | kN      | No                 |              |           |
| SD limit :                         | 45.0 % |                   |         | Yes                |              |           |
| Pre HSP                            |        | 40.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations         |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | None   |                   |         |                    |              |           |

### Pressure Data

|                      |            |    |       |            |    |            |    |
|----------------------|------------|----|-------|------------|----|------------|----|
| Mean Pre Pressure :  | 1.95       | kN | Min : | 1.92       | kN | Punch NO.; | 14 |
| SD :                 | 0.70       | %  | Max : | 1.99       | kN | Punch NO.; | 60 |
| Mean Main Pressure : | 12.52      | kN | Min : | 11.82      | kN | Punch NO.; | 37 |
| SD :                 | 3.00       | %  | Max : | 13.66      | kN | Punch NO.; | 60 |
| Filling Depth :      | Increase ; | 27 | Times | Decrease ; | 43 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 258720   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 10       | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.80    | mm  | Pre Thickness ;  | 2.81     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 4.95    | mm  | Main Thickness ; | 1.96     | mm           |
| Filling Depth :               | 6.23    | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.813   | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 30      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 21      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | On       |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.19 | kN |             |    |
|                  | Max ;     | 0.33 | kN | Max Punch ; | 23 |
| Lower Punch :    | Average ; | 0.13 | kN |             |    |
|                  | Max ;     | 0.15 | kN | Max Punch ; | 74 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                     |         |       |        |         |
|-----------------|---------------------|---------|-------|--------|---------|
| Total Counter : | 1172034             | Tablets |       |        |         |
| A.W.C Counter : | 1166036             | Tablets |       |        |         |
| HEP :           | 0 (0%)              | Tablets | LEP : | 0 (0%) | Tablets |
| GOOD :          | 1166036<br>(100.0%) | Tablets |       |        |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | SERTRA<br>50MG,STSH4A00 |
| User ID :        | pb97604       | Batch NO. :          | SHM2503250              |
| Print Interval : | 50000 Tablets | Running Time :       | 04 Hour 31 Min 47 Sec   |
| Total Counter :  | 1172034       | Total Running Time : | 2554 Hour 3 Min         |
| Station :        | Station 2     |                      |                         |

### Setting Value

|                                    |        |                   |         |                    |       |                      |
|------------------------------------|--------|-------------------|---------|--------------------|-------|----------------------|
| Feeder :                           | Auto ; | 37                | %       | Manual ;           | 40    | RPM                  |
| Filling Cam :                      |        | Cam B<br>4.5-10mm |         | Cam Range :        | Min : | 2.50 mm              |
| Target Quantity :                  |        | 6000000           | Tablets |                    | Max : | 8.00 mm              |
| Air Pressure Low Limit :           |        | 0.400             | MPa     |                    |       |                      |
| Oil Lubrication :                  |        |                   |         |                    |       |                      |
| Upper Punch Interval Time(S1) ;    |        | 50                | Min     | Supply Time ;      | 0.2   | Sec                  |
| Lower Punch Interval Time(S2) ;    |        | 50                | Min     | Supply Time ;      | 1.0   | Sec                  |
| Powder Supply Time :               |        | 60.0              | Sec     |                    |       |                      |
| Initial Reject Time :              |        | 2                 | Tablets |                    |       |                      |
| Upper Punch Tightness High Limit : |        | 2.00              | kN      |                    |       |                      |
| Lower Punch Tightness High Limit : |        | 3.00              | kN      |                    |       |                      |
| Ejecting Force High Limit :        |        | 4.90              | kN      |                    |       |                      |
|                                    |        |                   |         | Stop Condition ;   |       |                      |
| HSP :                              | 28.0 % | 15.43             | kN      | No                 |       |                      |
| HEP :                              | 23.0 % | 14.83             | kN      | Yes                | 10    | Rotations 15 Tablets |
| HCP :                              | 2.0 %  | 12.30             | kN      | Yes                | 15    | Times                |
| Ref :                              |        | 12.06             | kN      |                    |       |                      |
| LCP :                              | 2.0 %  | 11.81             | kN      | Yes                | 15    | Times                |
| LEP :                              | 23.0 % | 9.28              | kN      | Yes                | 10    | Rotations 15 Tablets |
| LSP :                              | 28.0 % | 8.68              | kN      | No                 |       |                      |
| SD limit :                         | 45.0 % |                   |         | Yes                |       |                      |
| Pre HSP                            |        | 40.00             | kN      | Yes                |       |                      |
| Mean Calculation range :           | 2      | Rotations         |         | Calculation Pass : | 2     | Rotations            |
| Empty Punch No. :                  | N      |                   |         |                    |       |                      |

### Pressure Data

|                      |            |    |       |            |    |            |    |
|----------------------|------------|----|-------|------------|----|------------|----|
| Mean Pre Pressure :  | 1.71       | kN | Min : | 1.66       | kN | Punch NO.; | 48 |
| SD :                 | 1.40       | %  | Max : | 1.76       | kN | Punch NO.; | 22 |
| Mean Main Pressure : | 11.98      | kN | Min : | 10.81      | kN | Punch NO.; | 10 |
| SD :                 | 3.60       | %  | Max : | 12.84      | kN | Punch NO.; | 60 |
| Filling Depth :      | Increase ; | 19 | Times | Decrease ; | 27 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 258720   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 10       | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.80    | mm  | Pre Thickness ;  | 2.81     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.00    | mm  | Main Thickness ; | 2.01     | mm           |
| Filling Depth :               | 5.96    | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.813   | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 30      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 21      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | On       |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.19 | kN |             |    |
|                  | Max ;     | 0.34 | kN | Max Punch ; | 22 |
| Lower Punch :    | Average ; | 0.13 | kN |             |    |
|                  | Max ;     | 0.15 | kN | Max Punch ; | 74 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                     |         |       |        |         |
|-----------------|---------------------|---------|-------|--------|---------|
| Total Counter : | 1172034             | Tablets |       |        |         |
| A.W.C Counter : | 1166036             | Tablets |       |        |         |
| HEP :           | 0 (0%)              | Tablets | LEP : | 0 (0%) | Tablets |
| GOOD :          | 1166036<br>(100.0%) | Tablets |       |        |         |