

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	sj97904	Batch NO. :	SHM2503250
Print Interval :	50000 Tablets	Running Time :	18 Hour 37 Min 36 Sec
Total Counter :	4824750	Total Running Time :	2568 Hour 9 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	39	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	16.01	kN	No		
HEP :	23.0 %	15.38	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.76	kN	Yes 15	Times	
Ref :		12.51	kN			
LCP :	2.0 %	12.26	kN	Yes 15	Times	
LEP :	23.0 %	9.63	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	9.01	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.90	kN	Min :	1.86	kN	Punch NO.;	17
SD :	0.80	%	Max :	1.94	kN	Punch NO.;	12
Mean Main Pressure :	12.52	kN	Min :	11.38	kN	Punch NO.;	23
SD :	3.70	%	Max :	13.60	kN	Punch NO.;	68
Filling Depth :	Increase ;	35	Times	Decrease ;	50	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.95	mm	Main Thickness ;	1.96	mm
Filling Depth :	6.23	mm	Current Cam :	Cam B	
Main Air pressure :	0.792	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	35	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.32	kN	Max Punch ;	65
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.16	kN	Max Punch ;	34
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	4824750	Tablets			
A.W.C Counter :	4817796	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	4817795 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	sj97904	Batch NO. :	SHM2503250
Print Interval :	50000 Tablets	Running Time :	18 Hour 37 Min 36 Sec
Total Counter :	4824750	Total Running Time :	2568 Hour 9 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	37	%	Manual ;	40	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	15.50	kN	No		
HEP :	23.0 %	14.89	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.35	kN	Yes 15	Times	
Ref :		12.11	kN			
LCP :	2.0 %	11.87	kN	Yes 15	Times	
LEP :	23.0 %	9.32	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	8.72	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.71	kN	Min :	1.65	kN	Punch NO.;	37
SD :	1.40	%	Max :	1.75	kN	Punch NO.;	59
Mean Main Pressure :	12.03	kN	Min :	11.14	kN	Punch NO.;	23
SD :	3.40	%	Max :	13.13	kN	Punch NO.;	60
Filling Depth :	Increase ;	41	Times	Decrease ;	50	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.00	mm	Main Thickness ;	2.01	mm
Filling Depth :	6.02	mm	Current Cam :	Cam B	
Main Air pressure :	0.792	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	35	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.32	kN	Max Punch ;	65
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.16	kN	Max Punch ;	34
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	4824750	Tablets			
A.W.C Counter :	4817873	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	4817872 (100.0%)	Tablets			