

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	cb83530	Batch NO. :	SHM2503450
Print Interval :	50000 Tablets	Running Time :	00 Hour 58 Min 02 Sec
Total Counter :	250302	Total Running Time :	2573 Hour 19 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	39	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	13.72	kN	No		
HEP :	23.0 %	13.18	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.93	kN	Yes 15	Times	
Ref :		10.72	kN			
LCP :	2.0 %	10.50	kN	Yes 15	Times	
LEP :	23.0 %	8.25	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	7.72	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.93	kN	Min :	1.89	kN	Punch NO.;	41
SD :	0.80	%	Max :	1.99	kN	Punch NO.;	59
Mean Main Pressure :	10.65	kN	Min :	9.95	kN	Punch NO.;	35
SD :	3.20	%	Max :	11.60	kN	Punch NO.;	69
Filling Depth :	Increase ; 2	Times	Decrease ; 5	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.98	mm	Main Thickness ;	1.99	mm
Filling Depth :	6.16	mm	Current Cam :	Cam B	
Main Air pressure :	0.819	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	35	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.31	kN	Max Punch ;	23
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.16	kN	Max Punch ;	14
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	250302	Tablets			
A.W.C Counter :	245689	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	245689 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	cb83530	Batch NO. :	SHM2503450
Print Interval :	50000 Tablets	Running Time :	00 Hour 58 Min 02 Sec
Total Counter :	250302	Total Running Time :	2573 Hour 19 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	39	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	13.31	kN	No		
HEP :	23.0 %	12.79	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	10.61	kN	Yes	15	Times
Ref :		10.40	kN			
LCP :	2.0 %	10.19	kN	Yes	15	Times
LEP :	23.0 %	8.01	kN	Yes	10	Rotations 15 Tablets
LSP :	28.0 %	7.49	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.72	kN	Min :	1.67	kN	Punch NO.;	57
SD :	1.30	%	Max :	1.78	kN	Punch NO.;	71
Mean Main Pressure :	10.44	kN	Min :	9.60	kN	Punch NO.;	36
SD :	3.70	%	Max :	11.48	kN	Punch NO.;	38
Filling Depth :	Increase ;	2	Times	Decrease ;	6	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.03	mm	Main Thickness ;	2.04	mm
Filling Depth :	5.98	mm	Current Cam :	Cam B	
Main Air pressure :	0.819	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	35	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.31	kN	Max Punch ;	23
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.16	kN	Max Punch ;	14
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	250302	Tablets			
A.W.C Counter :	245689	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	245689 (100.0%)	Tablets			