

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	vy190186	Batch NO. :	SHM2503450
Print Interval :	50000 Tablets	Running Time :	02 Hour 53 Min 54 Sec
Total Counter :	750584	Total Running Time :	2575 Hour 15 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	39	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	13.83	kN	No		
HEP :	23.0 %	13.29	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.02	kN	Yes 15	Times	
Ref :		10.80	kN			
LCP :	2.0 %	10.59	kN	Yes 15	Times	
LEP :	23.0 %	8.32	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	7.78	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.93	kN	Min :	1.89	kN	Punch NO.;	24
SD :	0.80	%	Max :	1.97	kN	Punch NO.;	63
Mean Main Pressure :	10.82	kN	Min :	9.90	kN	Punch NO.;	26
SD :	4.00	%	Max :	11.81	kN	Punch NO.;	69
Filling Depth :	Increase ;	6	Times	Decrease ;	7	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.01	mm	Main Thickness ;	2.02	mm
Filling Depth :	6.31	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.800	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	35	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.32	kN	Max Punch ;	26
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.15	kN	Max Punch ;	14
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	750584	Tablets			
A.W.C Counter :	745815	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	745815 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	vy190186	Batch NO. :	SHM2503450
Print Interval :	50000 Tablets	Running Time :	02 Hour 53 Min 54 Sec
Total Counter :	750584	Total Running Time :	2575 Hour 15 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	39	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	13.31	kN	No		
HEP :	23.0 %	12.79	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.61	kN	Yes 15	Times	
Ref :		10.40	kN			
LCP :	2.0 %	10.19	kN	Yes 15	Times	
LEP :	23.0 %	8.01	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	7.49	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.69	kN	Min :	1.63	kN	Punch NO.;	37
SD :	1.30	%	Max :	1.75	kN	Punch NO.;	62
Mean Main Pressure :	10.39	kN	Min :	9.55	kN	Punch NO.;	10
SD :	3.70	%	Max :	11.14	kN	Punch NO.;	56
Filling Depth :	Increase ;	4	Times	Decrease ;	8	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.06	mm	Main Thickness ;	2.07	mm
Filling Depth :	5.98	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.800	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	35	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.22	kN		
	Max ;	0.31	kN	Max Punch ;	28
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.15	kN	Max Punch ;	14
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	750584	Tablets			
A.W.C Counter :	745815	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	745815 (100.0%)	Tablets			