

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	sj97904	Batch NO. :	SHM2503450
Print Interval :	50000 Tablets	Running Time :	12 Hour 56 Min 30 Sec
Total Counter :	3352780	Total Running Time :	2585 Hour 18 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	40	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	13.69	kN	No		
HEP :	23.0 %	13.15	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.91	kN	Yes 15	Times	
Ref :		10.69	kN			
LCP :	2.0 %	10.48	kN	Yes 15	Times	
LEP :	23.0 %	8.23	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	7.70	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.91	kN	Min :	1.86	kN	Punch NO.;	24
SD :	0.90	%	Max :	1.95	kN	Punch NO.;	63
Mean Main Pressure :	10.73	kN	Min :	9.79	kN	Punch NO.;	23
SD :	3.70	%	Max :	11.79	kN	Punch NO.;	65
Filling Depth :	Increase ;	42	Times	Decrease ;	40	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.01	mm	Main Thickness ;	2.02	mm
Filling Depth :	6.29	mm	Current Cam :	Cam B	
Main Air pressure :	0.801	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	41	Min			
Lower Punch Remain Time (S2):	32	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.28	kN		
	Max ;	0.41	kN	Max Punch ;	77
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.16	kN	Max Punch ;	34
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3352780	Tablets			
A.W.C Counter :	3347222	Tablets			
HEP :	0 (0%)	Tablets	LEP :	358 (0.0%)	Tablets
GOOD :	3346864 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	sj97904	Batch NO. :	SHM2503450
Print Interval :	50000 Tablets	Running Time :	12 Hour 56 Min 30 Sec
Total Counter :	3352780	Total Running Time :	2585 Hour 18 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	39	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	13.84	kN	No		
HEP :	23.0 %	13.30	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.03	kN	Yes 15	Times	
Ref :		10.81	kN			
LCP :	2.0 %	10.59	kN	Yes 15	Times	
LEP :	23.0 %	8.32	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	7.78	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.71	kN	Min :	1.66	kN	Punch NO.;	10
SD :	1.40	%	Max :	1.77	kN	Punch NO.;	27
Mean Main Pressure :	10.71	kN	Min :	9.57	kN	Punch NO.;	10
SD :	4.30	%	Max :	11.61	kN	Punch NO.;	46
Filling Depth :	Increase ;	52	Times	Decrease ;	37	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.06	mm	Main Thickness ;	2.07	mm
Filling Depth :	6.03	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.801	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	41	Min			
Lower Punch Remain Time (S2):	32	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.28	kN		
	Max ;	0.45	kN	Max Punch ;	65
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.16	kN	Max Punch ;	34
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3352780	Tablets			
A.W.C Counter :	3347299	Tablets			
HEP :	0 (0%)	Tablets	LEP :	358 (0.0%)	Tablets
GOOD :	3346941 (100.0%)	Tablets			