

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	sj97904	Batch NO. :	SHM2503450
Print Interval :	50000 Tablets	Running Time :	15 Hour 27 Min 15 Sec
Total Counter :	4003324	Total Running Time :	2587 Hour 49 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	34	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	13.69	kN	No		
HEP :	23.0 %	13.15	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.91	kN	Yes 15	Times	
Ref :		10.69	kN			
LCP :	2.0 %	10.48	kN	Yes 15	Times	
LEP :	23.0 %	8.23	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	7.70	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.89	kN	Min :	1.85	kN	Punch NO.;	14
SD :	1.00	%	Max :	1.94	kN	Punch NO.;	63
Mean Main Pressure :	10.71	kN	Min :	9.71	kN	Punch NO.;	36
SD :	4.00	%	Max :	11.76	kN	Punch NO.;	73
Filling Depth :	Increase ; 46	Times	Decrease ; 40	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.01	mm	Main Thickness ;	2.02	mm
Filling Depth :	6.29	mm	Current Cam :	Cam B	
Main Air pressure :	0.815	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	41	Min			
Lower Punch Remain Time (S2):	32	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.75	kN		
	Max ;	1.28	kN	Max Punch ;	26
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.16	kN	Max Punch ;	34
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	4003324	Tablets			
A.W.C Counter :	3997680	Tablets			
HEP :	0 (0%)	Tablets	LEP :	426 (0.0%)	Tablets
GOOD :	3997254 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG,STSH4A00
User ID :	sj97904	Batch NO. :	SHM2503450
Print Interval :	50000 Tablets	Running Time :	15 Hour 27 Min 15 Sec
Total Counter :	4003324	Total Running Time :	2587 Hour 49 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	34	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	28.0 %	13.84	kN	No		
HEP :	23.0 %	13.30	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.03	kN	Yes 15	Times	
Ref :		10.81	kN			
LCP :	2.0 %	10.59	kN	Yes 15	Times	
LEP :	23.0 %	8.32	kN	Yes 10	Rotations 15	Tablets
LSP :	28.0 %	7.78	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.69	kN	Min :	1.63	kN	Punch NO.;	25
SD :	1.70	%	Max :	1.76	kN	Punch NO.;	31
Mean Main Pressure :	10.88	kN	Min :	9.79	kN	Punch NO.;	36
SD :	4.30	%	Max :	11.96	kN	Punch NO.;	2
Filling Depth :	Increase ;	74	Times	Decrease ;	45	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.06	mm	Main Thickness ;	2.07	mm
Filling Depth :	6.00	mm	Current Cam :	Cam B	
Main Air pressure :	0.815	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	41	Min			
Lower Punch Remain Time (S2):	32	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.75	kN		
	Max ;	1.28	kN	Max Punch ;	26
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.16	kN	Max Punch ;	34
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	4003324	Tablets			
A.W.C Counter :	3997680	Tablets			
HEP :	0 (0%)	Tablets	LEP :	426 (0.0%)	Tablets
GOOD :	3997254 (100.0%)	Tablets			