

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	rp98927	Batch NO. :	IUM2503960
Print Interval :	50000 Tablets	Running Time :	05 Hour 48 Min 38 Sec
Total Counter :	550214	Total Running Time :	2600 Hour 59 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	240	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.26	kN	No		
HEP :	25.0 %	35.82	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.23	kN	Yes 15	Times	
Ref :		28.66	kN			
LCP :	2.0 %	28.09	kN	Yes 15	Times	
LEP :	25.0 %	21.49	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.06	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.51	kN	Min :	2.37	kN	Punch NO.;	9
SD :	2.60	%	Max :	2.66	kN	Punch NO.;	41
Mean Main Pressure :	28.58	kN	Min :	24.95	kN	Punch NO.;	17
SD :	5.90	%	Max :	32.76	kN	Punch NO.;	50
Filling Depth :	Increase ; 166	Times	Decrease ;	170	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	36	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.40	mm	Pre Thickness ;	5.40	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.34	mm	Main Thickness ;	4.34	mm
Filling Depth :	10.36	mm	Current Cam :	Cam C	
Main Air pressure :	0.814	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	13
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	51
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550214	Tablets			
A.W.C Counter :	544768	Tablets			
HEP :	546 (0.1%)	Tablets	LEP :	50 (0.0%)	Tablets
GOOD :	544172 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	rp98927	Batch NO. :	IUM2503960
Print Interval :	50000 Tablets	Running Time :	05 Hour 48 Min 38 Sec
Total Counter :	550214	Total Running Time :	2600 Hour 59 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	244	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	39.53	kN	No		
HEP :	25.0 %	38.01	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	31.01	kN	Yes 15	Times	
Ref :		30.40	kN			
LCP :	2.0 %	29.80	kN	Yes 15	Times	
LEP :	25.0 %	22.80	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.28	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.18	kN	Min :	2.05	kN	Punch NO.;	7
SD :	2.90	%	Max :	2.31	kN	Punch NO.;	50
Mean Main Pressure :	30.47	kN	Min :	26.85	kN	Punch NO.;	17
SD :	6.40	%	Max :	34.33	kN	Punch NO.;	50
Filling Depth :	Increase ;	217	Times	Decrease ;	176	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	37	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.50	mm	Pre Thickness ;	5.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.45	mm	Main Thickness ;	4.45	mm
Filling Depth :	10.40	mm	Current Cam :	Cam C	
Main Air pressure :	0.814	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	13
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	12
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550214	Tablets			
A.W.C Counter :	544768	Tablets			
HEP :	546 (0.1%)	Tablets	LEP :	50 (0.0%)	Tablets
GOOD :	544172 (99.9%)	Tablets			