

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	rp98927	Batch NO. :	IUM2503960
Print Interval :	50000 Tablets	Running Time :	06 Hour 51 Min 56 Sec
Total Counter :	650230	Total Running Time :	2602 Hour 2 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	244	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.56	kN	No		
HEP :	25.0 %	37.08	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.26	kN	Yes 15	Times	
Ref :		29.67	kN			
LCP :	2.0 %	29.07	kN	Yes 15	Times	
LEP :	25.0 %	22.25	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.77	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.55	kN	Min :	2.39	kN	Punch NO.;	27
SD :	2.60	%	Max :	2.71	kN	Punch NO.;	53
Mean Main Pressure :	29.72	kN	Min :	25.51	kN	Punch NO.;	17
SD :	5.20	%	Max :	33.41	kN	Punch NO.;	41
Filling Depth :	Increase ;	215	Times	Decrease ;	214	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	37	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.40	mm	Pre Thickness ;	5.40	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.34	mm	Main Thickness ;	4.34	mm
Filling Depth :	10.48	mm	Current Cam :	Cam C	
Main Air pressure :	0.819	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	50	Min			
Lower Punch Remain Time (S2):	41	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	11
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	43
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	650230	Tablets			
A.W.C Counter :	644605	Tablets			
HEP :	624 (0.1%)	Tablets	LEP :	63 (0.0%)	Tablets
GOOD :	643918 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	rp98927	Batch NO. :	IUM2503960
Print Interval :	50000 Tablets	Running Time :	06 Hour 51 Min 56 Sec
Total Counter :	650230	Total Running Time :	2602 Hour 2 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	264	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	39.53	kN	No		
HEP :	25.0 %	38.01	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	31.01	kN	Yes 15	Times	
Ref :		30.40	kN			
LCP :	2.0 %	29.80	kN	Yes 15	Times	
LEP :	25.0 %	22.80	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.28	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.17	kN	Min :	2.02	kN	Punch NO.;	17
SD :	3.50	%	Max :	2.35	kN	Punch NO.;	41
Mean Main Pressure :	30.39	kN	Min :	25.65	kN	Punch NO.;	17
SD :	6.90	%	Max :	35.43	kN	Punch NO.;	41
Filling Depth :	Increase ;	284	Times	Decrease ;	241	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	40	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.50	mm	Pre Thickness ;	5.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.45	mm	Main Thickness ;	4.45	mm
Filling Depth :	10.56	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.819	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	50	Min			
Lower Punch Remain Time (S2):	41	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	11
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	43
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	650230	Tablets			
A.W.C Counter :	644605	Tablets			
HEP :	624 (0.1%)	Tablets	LEP :	63 (0.0%)	Tablets
GOOD :	643918 (99.9%)	Tablets			