

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | IBU BP600MG<br>STIU2C00 |
| User ID :        | rp98927       | Batch NO. :          | IUM2503960              |
| Print Interval : | 50000 Tablets | Running Time :       | 07 Hour 23 Min 35 Sec   |
| Total Counter :  | 700234        | Total Running Time : | 2602 Hour 34 Min        |
| Station :        | Station 1     |                      |                         |

### Setting Value

|                                    |             |                   |         |                    |              |           |
|------------------------------------|-------------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 244               | %       | Manual ;           | 20           | RPM       |
| Filling Cam :                      |             | Cam C<br>8.5-14mm |         | Cam Range :        | Min :        | 6.50 mm   |
| Target Quantity :                  |             | 1350000           | Tablets |                    | Max :        | 12.00 mm  |
| Air Pressure Low Limit :           |             | 0.000             | MPa     |                    |              |           |
| Oil Lubrication :                  |             |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 50                | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 50                | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |             | 60.0              | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 2.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 3.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.90              | kN      |                    |              |           |
|                                    |             |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 38.56             | kN      | No                 |              |           |
| HEP :                              | 25.0 %      | 37.08             | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %       | 30.26             | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 29.67             | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 29.07             | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 %      | 22.25             | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 %      | 20.77             | kN      | No                 |              |           |
| SD limit :                         | 45.0 %      |                   |         | Yes                |              |           |
| Pre HSP                            |             | 40.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |                   |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | None        |                   |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 2.53       | kN  | Min : | 2.40       | kN  | Punch NO.; | 14 |
| SD :                 | 2.50       | %   | Max : | 2.65       | kN  | Punch NO.; | 51 |
| Mean Main Pressure : | 29.37      | kN  | Min : | 26.36      | kN  | Punch NO.; | 15 |
| SD :                 | 5.00       | %   | Max : | 32.09      | kN  | Punch NO.; | 44 |
| Filling Depth :      | Increase ; | 226 | Times | Decrease ; | 232 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 15      | RPM | Capacity :       | 95400    | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 37       | RPM          |
| Pre Upper Punch Position ;    | 3.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 8.40    | mm  | Pre Thickness ;  | 5.40     | mm           |
| Main Upper Punch Position ;   | 3.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 7.34    | mm  | Main Thickness ; | 4.34     | mm           |
| Filling Depth :               | 10.27   | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.820   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 18      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 9       | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.07 | kN |             |    |
|                  | Max ;     | 0.11 | kN | Max Punch ; | 11 |
| Lower Punch :    | Average ; | 0.06 | kN |             |    |
|                  | Max ;     | 0.08 | kN | Max Punch ; | 38 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                   |         |       |           |         |
|-----------------|-------------------|---------|-------|-----------|---------|
| Total Counter : | 700234            | Tablets |       |           |         |
| A.W.C Counter : | 694584            | Tablets |       |           |         |
| HEP :           | 642 (0.1%)        | Tablets | LEP : | 64 (0.0%) | Tablets |
| GOOD :          | 693878<br>(99.9%) | Tablets |       |           |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | IBU BP600MG<br>STIU2C00 |
| User ID :        | rp98927       | Batch NO. :          | IUM2503960              |
| Print Interval : | 50000 Tablets | Running Time :       | 07 Hour 23 Min 35 Sec   |
| Total Counter :  | 700234        | Total Running Time : | 2602 Hour 34 Min        |
| Station :        | Station 2     |                      |                         |

### Setting Value

|                                    |        |           |         |                    |              |           |
|------------------------------------|--------|-----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 264       | %       | Manual ;           | 15           | RPM       |
| Filling Cam :                      |        | Cam C     |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |        | 8.5-14mm  |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |        | 1350000   | Tablets |                    |              |           |
| Air Pressure Low Limit :           |        | 0.000     | MPa     |                    |              |           |
| Oil Lubrication :                  |        |           |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 50        | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 50        | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |        | 60.0      | Sec     |                    |              |           |
| Initial Reject Time :              |        | 2         | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 2.00      | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 3.00      | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.90      | kN      |                    |              |           |
|                                    |        |           |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 % | 39.53     | kN      | No                 |              |           |
| HEP :                              | 25.0 % | 38.01     | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 31.01     | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 30.40     | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 29.80     | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 % | 22.80     | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 % | 21.28     | kN      | No                 |              |           |
| SD limit :                         | 45.0 % |           |         | Yes                |              |           |
| Pre HSP                            |        | 40.00     | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | N      |           |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 2.13       | kN  | Min : | 1.99       | kN  | Punch NO.; | 7  |
| SD :                 | 3.50       | %   | Max : | 2.33       | kN  | Punch NO.; | 41 |
| Mean Main Pressure : | 29.61      | kN  | Min : | 24.35      | kN  | Punch NO.; | 17 |
| SD :                 | 7.40       | %   | Max : | 34.90      | kN  | Punch NO.; | 41 |
| Filling Depth :      | Increase ; | 304 | Times | Decrease ; | 261 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 15      | RPM | Capacity :       | 95400    | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 40       | RPM          |
| Pre Upper Punch Position ;    | 3.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 8.50    | mm  | Pre Thickness ;  | 5.50     | mm           |
| Main Upper Punch Position ;   | 3.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 7.45    | mm  | Main Thickness ; | 4.45     | mm           |
| Filling Depth :               | 10.56   | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.820   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 18      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 9       | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.07 | kN |             |    |
|                  | Max ;     | 0.11 | kN | Max Punch ; | 11 |
| Lower Punch :    | Average ; | 0.06 | kN |             |    |
|                  | Max ;     | 0.08 | kN | Max Punch ; | 38 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                |         |       |           |         |
|-----------------|----------------|---------|-------|-----------|---------|
| Total Counter : | 700234         | Tablets |       |           |         |
| A.W.C Counter : | 694584         | Tablets |       |           |         |
| HEP :           | 642 (0.1%)     | Tablets | LEP : | 64 (0.0%) | Tablets |
| GOOD :          | 693878 (99.9%) | Tablets |       |           |         |