

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	pb97604	Batch NO. :	IUM2503960
Print Interval :	50000 Tablets	Running Time :	11 Hour 36 Min 49 Sec
Total Counter :	1100348	Total Running Time :	2606 Hour 47 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	248	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.83	kN	No		
HEP :	25.0 %	36.38	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.68	kN	Yes 15	Times	
Ref :		29.10	kN			
LCP :	2.0 %	28.52	kN	Yes 15	Times	
LEP :	25.0 %	21.83	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.37	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.48	kN	Min :	2.35	kN	Punch NO.;	9
SD :	2.00	%	Max :	2.60	kN	Punch NO.;	50
Mean Main Pressure :	29.46	kN	Min :	26.36	kN	Punch NO.;	9
SD :	4.90	%	Max :	32.50	kN	Punch NO.;	41
Filling Depth :	Increase ;	357	Times	Decrease ;	379	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	37	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.40	mm	Pre Thickness ;	5.40	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.34	mm	Main Thickness ;	4.34	mm
Filling Depth :	9.72	mm	Current Cam :	Cam C	
Main Air pressure :	0.829	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	11
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	44
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1100348	Tablets			
A.W.C Counter :	1093910	Tablets			
HEP :	857 (0.1%)	Tablets	LEP :	123 (0.0%)	Tablets
GOOD :	1092930 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	pb97604	Batch NO. :	IUM2503960
Print Interval :	50000 Tablets	Running Time :	11 Hour 36 Min 49 Sec
Total Counter :	1100348	Total Running Time :	2606 Hour 47 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	264	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		50	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	39.50	kN	No		
HEP :	25.0 %	37.98	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.99	kN	Yes 15	Times	
Ref :		30.38	kN			
LCP :	2.0 %	29.78	kN	Yes 15	Times	
LEP :	25.0 %	22.79	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.27	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.12	kN	Min :	2.02	kN	Punch NO.;	10
SD :	2.70	%	Max :	2.26	kN	Punch NO.;	41
Mean Main Pressure :	30.17	kN	Min :	24.91	kN	Punch NO.;	17
SD :	6.30	%	Max :	33.91	kN	Punch NO.;	41
Filling Depth :	Increase ;	416	Times	Decrease ;	374	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	40	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.50	mm	Pre Thickness ;	5.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.45	mm	Main Thickness ;	4.45	mm
Filling Depth :	10.38	mm	Current Cam :	Cam C	
Main Air pressure :	0.829	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	11
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	44
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1100348	Tablets			
A.W.C Counter :	1093910	Tablets			
HEP :	857 (0.1%)	Tablets	LEP :	123 (0.0%)	Tablets
GOOD :	1092930 (99.9%)	Tablets			