

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	rp98927	Batch NO. :	IUM2504060
Print Interval :	50000 Tablets	Running Time :	01 Hour 35 Min 06 Sec
Total Counter :	150030	Total Running Time :	2610 Hour 47 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	284	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.79	kN	No		
HEP :	25.0 %	36.34	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.65	kN	Yes 15	Times	
Ref :		29.07	kN			
LCP :	2.0 %	28.49	kN	Yes 15	Times	
LEP :	25.0 %	21.80	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.35	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.56	kN	Min :	2.46	kN	Punch NO.;	9
SD :	2.10	%	Max :	2.70	kN	Punch NO.;	50
Mean Main Pressure :	29.76	kN	Min :	25.77	kN	Punch NO.;	17
SD :	5.00	%	Max :	33.14	kN	Punch NO.;	50
Filling Depth :	Increase ;	35	Times	Decrease ;	44	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	43	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.40	mm	Pre Thickness ;	5.41	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.34	mm	Main Thickness ;	4.34	mm
Filling Depth :	9.88	mm	Current Cam :	Cam C	
Main Air pressure :	0.815	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	11
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	150030	Tablets			
A.W.C Counter :	148156	Tablets			
HEP :	8 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	148148 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	rp98927	Batch NO. :	IUM2504060
Print Interval :	50000 Tablets	Running Time :	01 Hour 35 Min 06 Sec
Total Counter :	150030	Total Running Time :	2610 Hour 47 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	309	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.84	kN	No		
HEP :	25.0 %	37.35	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.48	kN	Yes 15	Times	
Ref :		29.88	kN			
LCP :	2.0 %	29.28	kN	Yes 15	Times	
LEP :	25.0 %	22.41	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.91	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.18	kN	Min :	2.08	kN	Punch NO.;	17
SD :	2.10	%	Max :	2.29	kN	Punch NO.;	35
Mean Main Pressure :	29.85	kN	Min :	25.27	kN	Punch NO.;	17
SD :	5.40	%	Max :	33.92	kN	Punch NO.;	44
Filling Depth :	Increase ;	21	Times	Decrease ;	26	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	46	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.49	mm	Pre Thickness ;	5.49	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.44	mm	Main Thickness ;	4.45	mm
Filling Depth :	10.37	mm	Current Cam :	Cam C	
Main Air pressure :	0.815	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	10
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	150030	Tablets			
A.W.C Counter :	148156	Tablets			
HEP :	8 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	148148 (100.0%)	Tablets			