

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	rp98927	Batch NO. :	IUM2504060
Print Interval :	50000 Tablets	Running Time :	02 Hour 06 Min 47 Sec
Total Counter :	200052	Total Running Time :	2611 Hour 18 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	284	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.79	kN	No		
HEP :	25.0 %	36.34	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.65	kN	Yes 15	Times	
Ref :		29.07	kN			
LCP :	2.0 %	28.49	kN	Yes 15	Times	
LEP :	25.0 %	21.80	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.35	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.51	kN	Min :	2.42	kN	Punch NO.;	12
SD :	1.80	%	Max :	2.61	kN	Punch NO.;	41
Mean Main Pressure :	28.76	kN	Min :	25.58	kN	Punch NO.;	17
SD :	4.60	%	Max :	31.40	kN	Punch NO.;	41
Filling Depth :	Increase ;	52	Times	Decrease ;	47	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	43	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.40	mm	Pre Thickness ;	5.41	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.34	mm	Main Thickness ;	4.34	mm
Filling Depth :	10.30	mm	Current Cam :	Cam C	
Main Air pressure :	0.786	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	11
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	43
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	200052	Tablets			
A.W.C Counter :	198188	Tablets			
HEP :	8 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	198180 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	rp98927	Batch NO. :	IUM2504060
Print Interval :	50000 Tablets	Running Time :	02 Hour 06 Min 47 Sec
Total Counter :	200052	Total Running Time :	2611 Hour 18 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	309	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.84	kN	No		
HEP :	25.0 %	37.35	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.48	kN	Yes 15	Times	
Ref :		29.88	kN			
LCP :	2.0 %	29.28	kN	Yes 15	Times	
LEP :	25.0 %	22.41	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.91	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.15	kN	Min :	2.06	kN	Punch NO.;	12
SD :	2.10	%	Max :	2.25	kN	Punch NO.;	35
Mean Main Pressure :	29.30	kN	Min :	25.77	kN	Punch NO.;	17
SD :	4.90	%	Max :	32.01	kN	Punch NO.;	50
Filling Depth :	Increase ;	26	Times	Decrease ;	30	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	46	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.49	mm	Pre Thickness ;	5.49	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.44	mm	Main Thickness ;	4.45	mm
Filling Depth :	10.40	mm	Current Cam :	Cam C	
Main Air pressure :	0.786	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	11
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	43
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	200052	Tablets			
A.W.C Counter :	198188	Tablets			
HEP :	8 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	198180 (100.0%)	Tablets			