

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	rp98927	Batch NO. :	IUM2504160
Print Interval :	50000 Tablets	Running Time :	03 Hour 53 Min 56 Sec
Total Counter :	350116	Total Running Time :	2627 Hour 33 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	280	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	35.83	kN	No		
HEP :	25.0 %	34.45	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.11	kN	Yes 15	Times	
Ref :		27.56	kN			
LCP :	2.0 %	27.01	kN	Yes 15	Times	
LEP :	25.0 %	20.67	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.29	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.57	kN	Min :	2.46	kN	Punch NO.;	9
SD :	1.90	%	Max :	2.68	kN	Punch NO.;	48
Mean Main Pressure :	28.58	kN	Min :	25.17	kN	Punch NO.;	17
SD :	4.50	%	Max :	31.16	kN	Punch NO.;	44
Filling Depth :	Increase ;	696	Times	Decrease ;	657	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	42	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.40	mm	Pre Thickness ;	5.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.45	mm	Main Thickness ;	4.46	mm
Filling Depth :	10.30	mm	Current Cam :	Cam C	
Main Air pressure :	0.822	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	42	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	1
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	36
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	350116	Tablets			
A.W.C Counter :	347816	Tablets			
HEP :	246 (0.1%)	Tablets	LEP :	41 (0.0%)	Tablets
GOOD :	347529 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	rp98927	Batch NO. :	IUM2504160
Print Interval :	50000 Tablets	Running Time :	03 Hour 53 Min 56 Sec
Total Counter :	350116	Total Running Time :	2627 Hour 33 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	332	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	33.42	kN	No		
HEP :	25.0 %	32.13	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	26.22	kN	Yes 15	Times	
Ref :		25.71	kN			
LCP :	2.0 %	25.19	kN	Yes 15	Times	
LEP :	25.0 %	19.28	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	17.99	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.20	kN	Min :	2.10	kN	Punch NO.;	17
SD :	2.20	%	Max :	2.32	kN	Punch NO.;	51
Mean Main Pressure :	25.50	kN	Min :	21.66	kN	Punch NO.;	17
SD :	5.60	%	Max :	28.41	kN	Punch NO.;	44
Filling Depth :	Increase ;	272	Times	Decrease ;	215	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	50	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.49	mm	Pre Thickness ;	5.50	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.61	mm	Main Thickness ;	4.62	mm
Filling Depth :	10.31	mm	Current Cam :	Cam C	
Main Air pressure :	0.822	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	42	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	13
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	36
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	350116	Tablets			
A.W.C Counter :	347816	Tablets			
HEP :	246 (0.1%)	Tablets	LEP :	41 (0.0%)	Tablets
GOOD :	347529 (99.9%)	Tablets			