

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	sj97904	Batch NO. :	IUM2504260
Print Interval :	50000 Tablets	Running Time :	13 Hour 55 Min 30 Sec
Total Counter :	1250300	Total Running Time :	2652 Hour 35 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	380	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	34.88	kN	No		
HEP :	25.0 %	33.53	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.36	kN	Yes 15	Times	
Ref :		26.83	kN			
LCP :	2.0 %	26.29	kN	Yes 15	Times	
LEP :	25.0 %	20.12	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.78	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.71	kN	Min :	2.60	kN	Punch NO.;	17
SD :	2.10	%	Max :	2.87	kN	Punch NO.;	29
Mean Main Pressure :	27.35	kN	Min :	24.41	kN	Punch NO.;	17
SD :	3.90	%	Max :	29.95	kN	Punch NO.;	50
Filling Depth :	Increase ;	1594	Times	Decrease ;	1589	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	60	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.25	mm	Pre Thickness ;	5.26	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.48	mm	Main Thickness ;	4.49	mm
Filling Depth :	10.74	mm	Current Cam :	Cam C	
Main Air pressure :	0.819	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	16
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	47
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1250300	Tablets			
A.W.C Counter :	1247950	Tablets			
HEP :	6 (0.0%)	Tablets	LEP :	91 (0.0%)	Tablets
GOOD :	1247853 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	sj97904	Batch NO. :	IUM2504260
Print Interval :	50000 Tablets	Running Time :	13 Hour 55 Min 30 Sec
Total Counter :	1250300	Total Running Time :	2652 Hour 35 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	394	%	Manual ;	23	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	32.77	kN	No		
HEP :	25.0 %	31.51	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	25.71	kN	Yes 15	Times	
Ref :		25.21	kN			
LCP :	2.0 %	24.70	kN	Yes 15	Times	
LEP :	25.0 %	18.91	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	17.65	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.22	kN	Min :	2.08	kN	Punch NO.;	21
SD :	3.10	%	Max :	2.39	kN	Punch NO.;	29
Mean Main Pressure :	24.72	kN	Min :	21.29	kN	Punch NO.;	21
SD :	6.10	%	Max :	27.89	kN	Punch NO.;	29
Filling Depth :	Increase ;	674	Times	Decrease ;	562	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	59	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.38	mm	Pre Thickness ;	5.39	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.60	mm	Main Thickness ;	4.61	mm
Filling Depth :	10.50	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.819	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	13
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	47
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1250300	Tablets			
A.W.C Counter :	1247950	Tablets			
HEP :	6 (0.0%)	Tablets	LEP :	91 (0.0%)	Tablets
GOOD :	1247853 (100.0%)	Tablets			