

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	pb97604	Batch NO. :	IUM2504360
Print Interval :	50000 Tablets	Running Time :	01 Hour 40 Min 17 Sec
Total Counter :	150032	Total Running Time :	2655 Hour 19 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	387	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	34.69	kN	No		
HEP :	25.0 %	33.36	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.22	kN	Yes 15	Times	
Ref :		26.69	kN			
LCP :	2.0 %	26.15	kN	Yes 15	Times	
LEP :	25.0 %	20.02	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.68	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.74	kN	Min :	2.60	kN	Punch NO.;	9
SD :	2.10	%	Max :	2.86	kN	Punch NO.;	41
Mean Main Pressure :	26.83	kN	Min :	23.90	kN	Punch NO.;	17
SD :	4.10	%	Max :	29.39	kN	Punch NO.;	50
Filling Depth :	Increase ;	1731	Times	Decrease ;	1690	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	58	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.25	mm	Pre Thickness ;	5.26	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.48	mm	Main Thickness ;	4.49	mm
Filling Depth :	10.30	mm	Current Cam :	Cam C	
Main Air pressure :	0.830	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	16
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	40
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	150032	Tablets			
A.W.C Counter :	148470	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	44 (0.0%)	Tablets
GOOD :	148425 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	pb97604	Batch NO. :	IUM2504360
Print Interval :	50000 Tablets	Running Time :	01 Hour 40 Min 17 Sec
Total Counter :	150032	Total Running Time :	2655 Hour 19 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	387	%	Manual ;	23	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	32.42	kN	No		
HEP :	25.0 %	31.17	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	25.44	kN	Yes 15	Times	
Ref :		24.94	kN			
LCP :	2.0 %	24.44	kN	Yes 15	Times	
LEP :	25.0 %	18.70	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	17.46	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.28	kN	Min :	2.12	kN	Punch NO.;	12
		2.80	%	Max :	2.42	kN	Punch NO.;	50
Mean Main Pressure :	SD :	24.79	kN	Min :	21.37	kN	Punch NO.;	17
		5.60	%	Max :	28.02	kN	Punch NO.;	50
Filling Depth :	Increase ;	756	Times	Decrease ;	607	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	58	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.38	mm	Pre Thickness ;	5.39	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.60	mm	Main Thickness ;	4.61	mm
Filling Depth :	10.40	mm	Current Cam :	Cam C	
Main Air pressure :	0.830	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	16
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	21
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	150032	Tablets			
A.W.C Counter :	148470	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	44 (0.0%)	Tablets
GOOD :	148425 (100.0%)	Tablets			