

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	rk99163	Batch NO. :	IUM2504460
Print Interval :	50000 Tablets	Running Time :	05 Hour 48 Min 51 Sec
Total Counter :	550118	Total Running Time :	2673 Hour 48 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	250	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	5.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	29.99	kN	No		
HEP :	25.0 %	28.84	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	23.53	kN	Yes 15	Times	
Ref :		23.07	kN			
LCP :	2.0 %	22.61	kN	Yes 15	Times	
LEP :	25.0 %	17.30	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	16.15	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.92	kN	Min :	3.89	kN	Punch NO.;	32
SD :	0.30	%	Max :	3.95	kN	Punch NO.;	40
Mean Main Pressure :	23.08	kN	Min :	21.66	kN	Punch NO.;	18
SD :	2.70	%	Max :	24.73	kN	Punch NO.;	12
Filling Depth :	Increase ;	128	Times	Decrease ;	129	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	38	RPM
Pre Upper Punch Position ;	3.98	mm			
Pre Lower Punch Position ;	8.60	mm	Pre Thickness ;	4.62	mm
Main Upper Punch Position ;	3.98	mm			
Main Lower Punch Position ;	8.42	mm	Main Thickness ;	4.44	mm
Filling Depth :	10.56	mm	Current Cam :	Cam C	
Main Air pressure :	0.827	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	38	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	2
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.07	kN	Max Punch ;	11
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550118	Tablets			
A.W.C Counter :	537313	Tablets			
HEP :	47 (0.0%)	Tablets	LEP :	131 (0.0%)	Tablets
GOOD :	537135 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU BP600MG STIU2C00
User ID :	rk99163	Batch NO. :	IUM2504460
Print Interval :	50000 Tablets	Running Time :	05 Hour 48 Min 51 Sec
Total Counter :	550118	Total Running Time :	2673 Hour 48 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	220	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	5.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	29.97	kN	No		
HEP :	25.0 %	28.81	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	23.51	kN	Yes 15	Times	
Ref :		23.05	kN			
LCP :	2.0 %	22.59	kN	Yes 15	Times	
LEP :	25.0 %	17.29	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	16.14	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.94	kN	Min :	3.90	kN	Punch NO.;	28
SD :	0.40	%	Max :	3.99	kN	Punch NO.;	53
Mean Main Pressure :	22.64	kN	Min :	20.99	kN	Punch NO.;	43
SD :	4.60	%	Max :	25.25	kN	Punch NO.;	27
Filling Depth :	Increase ;	86	Times	Decrease ;	68	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	33	RPM
Pre Upper Punch Position ;	4.01	mm			
Pre Lower Punch Position ;	8.60	mm	Pre Thickness ;	4.59	mm
Main Upper Punch Position ;	3.98	mm			
Main Lower Punch Position ;	8.42	mm	Main Thickness ;	4.44	mm
Filling Depth :	9.79	mm	Current Cam :	Cam C	
Main Air pressure :	0.827	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	38	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	2
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.07	kN	Max Punch ;	11
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550118	Tablets			
A.W.C Counter :	537313	Tablets			
HEP :	47 (0.0%)	Tablets	LEP :	131 (0.0%)	Tablets
GOOD :	537135 (100.0%)	Tablets			