

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	LEVET 500mg STLC2B00
User ID :	rp98927	Batch NO. :	LCM2507050
Print Interval :	50000 Tablets	Running Time :	00 Hour 31 Min 55 Sec
Total Counter :	50030	Total Running Time :	2682 Hour 45 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	166	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1320000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	5.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	45.06	kN	No		
HEP :	25.0 %	43.33	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	35.36	kN	Yes 15	Times	
Ref :		34.66	kN			
LCP :	2.0 %	33.97	kN	Yes 15	Times	
LEP :	25.0 %	26.00	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	24.26	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	8.32	kN	Min :	8.26	kN	Punch NO.;	42
SD :	0.40	%	Max :	8.40	kN	Punch NO.;	13
Mean Main Pressure :	34.81	kN	Min :	33.01	kN	Punch NO.;	30
SD :	2.60	%	Max :	38.68	kN	Punch NO.;	38
Filling Depth :	Increase ; 5	Times	Decrease ; 8	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.80	mm	Pre Thickness ;	3.80	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.15	mm	Main Thickness ;	3.15	mm
Filling Depth :	7.99	mm	Current Cam :	Cam C	
Main Air pressure :	0.829	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.12	kN	Max Punch ;	28
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	10
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	50030	Tablets			
A.W.C Counter :	46815	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	46815 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	LEVET 500mg STLC2B00
User ID :	rp98927	Batch NO. :	LCM2507050
Print Interval :	50000 Tablets	Running Time :	00 Hour 31 Min 55 Sec
Total Counter :	50030	Total Running Time :	2682 Hour 45 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	166	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1320000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	5.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	48.28	kN	No		
HEP :	25.0 %	46.42	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	37.88	kN	Yes 15	Times	
Ref :		37.14	kN			
LCP :	2.0 %	36.40	kN	Yes 15	Times	
LEP :	25.0 %	27.85	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	26.00	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	8.36	kN	Min :	8.30	kN	Punch NO.;	16
SD :	0.30	%	Max :	8.45	kN	Punch NO.;	53
Mean Main Pressure :	36.62	kN	Min :	35.10	kN	Punch NO.;	39
SD :	2.00	%	Max :	38.70	kN	Punch NO.;	38
Filling Depth :	Increase ;	2	Times	Decrease ;	5	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.80	mm	Pre Thickness ;	3.80	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.20	mm	Main Thickness ;	3.20	mm
Filling Depth :	8.09	mm	Current Cam :	Cam C	
Main Air pressure :	0.829	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.10	kN	Max Punch ;	28
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	10
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	50030	Tablets			
A.W.C Counter :	46815	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	46815 (100.0%)	Tablets			