

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	LEVET 500mg STLC2B00
User ID :	mr99799	Batch NO. :	LCM2507050
Print Interval :	50000 Tablets	Running Time :	09 Hour 31 Min 58 Sec
Total Counter :	902196	Total Running Time :	2691 Hour 45 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	166	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1320000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	5.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	47.57	kN	No		
HEP :	25.0 %	45.74	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	37.32	kN	Yes 15	Times	
Ref :		36.59	kN			
LCP :	2.0 %	35.86	kN	Yes 15	Times	
LEP :	25.0 %	27.44	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	25.61	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	8.29	kN	Min :	8.22	kN	Punch NO.;	16
SD :	0.40	%	Max :	8.35	kN	Punch NO.;	27
Mean Main Pressure :	36.46	kN	Min :	34.62	kN	Punch NO.;	50
SD :	2.20	%	Max :	38.46	kN	Punch NO.;	38
Filling Depth :	Increase ; 12	Times	Decrease ; 36	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.80	mm	Pre Thickness ;	3.81	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.15	mm	Main Thickness ;	3.15	mm
Filling Depth :	8.28	mm	Current Cam :	Cam C	
Main Air pressure :	0.756	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.11	kN	Max Punch ;	28
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	7
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	902196	Tablets			
A.W.C Counter :	896322	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	896322 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	LEVET 500mg STLC2B00
User ID :	mr99799	Batch NO. :	LCM2507050
Print Interval :	50000 Tablets	Running Time :	09 Hour 31 Min 58 Sec
Total Counter :	902196	Total Running Time :	2691 Hour 45 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	166	%	Manual ;	52	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1320000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	5.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	45.98	kN	No		
HEP :	25.0 %	44.21	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	36.08	kN	Yes 15	Times	
Ref :		35.37	kN			
LCP :	2.0 %	34.66	kN	Yes 15	Times	
LEP :	25.0 %	26.53	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	24.76	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	8.31	kN	Min :	8.24	kN	Punch NO.;	19
SD :	0.30	%	Max :	8.39	kN	Punch NO.;	52
Mean Main Pressure :	35.72	kN	Min :	33.51	kN	Punch NO.;	39
SD :	2.40	%	Max :	38.68	kN	Punch NO.;	7
Filling Depth :	Increase ;	6	Times	Decrease ;	13	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.80	mm	Pre Thickness ;	3.80	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.26	mm	Main Thickness ;	3.27	mm
Filling Depth :	8.01	mm	Current Cam :	Cam C	
Main Air pressure :	0.756	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.10	kN	Max Punch ;	28
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	7
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	902196	Tablets			
A.W.C Counter :	896322	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	896322 (100.0%)	Tablets			