

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	LEVET 500mg STLC2B00
User ID :	rp98927	Batch NO. :	LCM2507150
Print Interval :	50000 Tablets	Running Time :	07 Hour 55 Min 27 Sec
Total Counter :	750164	Total Running Time :	2704 Hour 4 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	166	%	Manual ;	23	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1320000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	5.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	48.00	kN	No		
HEP :	25.0 %	46.15	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	37.66	kN	Yes 15	Times	
Ref :		36.92	kN			
LCP :	2.0 %	36.18	kN	Yes 15	Times	
LEP :	25.0 %	27.69	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	25.84	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	8.26	kN	Min :	8.20	kN	Punch NO.;	32
SD :	0.30	%	Max :	8.33	kN	Punch NO.;	49
Mean Main Pressure :	36.96	kN	Min :	34.93	kN	Punch NO.;	50
SD :	2.70	%	Max :	39.93	kN	Punch NO.;	23
Filling Depth :	Increase ; 90	Times	Decrease ;	193	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.60	mm	Pre Thickness ;	3.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.15	mm	Main Thickness ;	3.16	mm
Filling Depth :	8.38	mm	Current Cam :	Cam C	
Main Air pressure :	0.755	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	39	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.11	kN	Max Punch ;	41
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	52
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	750164	Tablets			
A.W.C Counter :	749020	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	749020 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	LEVET 500mg STLC2B00
User ID :	rp98927	Batch NO. :	LCM2507150
Print Interval :	50000 Tablets	Running Time :	07 Hour 55 Min 27 Sec
Total Counter :	750164	Total Running Time :	2704 Hour 4 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	166	%	Manual ;	52	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1320000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	5.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	46.91	kN	No		
HEP :	25.0 %	45.11	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	36.81	kN	Yes 15	Times	
Ref :		36.09	kN			
LCP :	2.0 %	35.37	kN	Yes 15	Times	
LEP :	25.0 %	27.07	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	25.26	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	8.26	kN	Min :	8.20	kN	Punch NO.;	29
SD :	0.40	%	Max :	8.36	kN	Punch NO.;	50
Mean Main Pressure :	36.15	kN	Min :	34.46	kN	Punch NO.;	9
SD :	2.40	%	Max :	38.91	kN	Punch NO.;	23
Filling Depth :	Increase ;	21	Times	Decrease ;	52	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.60	mm	Pre Thickness ;	3.60	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.26	mm	Main Thickness ;	3.27	mm
Filling Depth :	7.95	mm	Current Cam :	Cam C	
Main Air pressure :	0.755	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	39	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.11	kN	Max Punch ;	41
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	3
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	750164	Tablets			
A.W.C Counter :	749020	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	749020 (100.0%)	Tablets			