

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	LEVET 500mg STLC2B00
User ID :	pb97604	Batch NO. :	LCM2507350
Print Interval :	50000 Tablets	Running Time :	01 Hour 03 Min 24 Sec
Total Counter :	100016	Total Running Time :	2724 Hour 51 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	190	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1320000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	47.03	kN	No		
HEP :	25.0 %	45.23	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	36.90	kN	Yes 15	Times	
Ref :		36.18	kN			
LCP :	2.0 %	35.46	kN	Yes 15	Times	
LEP :	25.0 %	27.14	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	25.33	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	8.42	kN	Min :	8.33	kN	Punch NO.;	41
SD :	0.50	%	Max :	8.51	kN	Punch NO.;	53
Mean Main Pressure :	36.15	kN	Min :	34.09	kN	Punch NO.;	50
SD :	2.30	%	Max :	38.35	kN	Punch NO.;	7
Filling Depth :	Increase ;	23	Times	Decrease ;	31	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.60	mm	Pre Thickness ;	3.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.21	mm	Main Thickness ;	3.22	mm
Filling Depth :	8.82	mm	Current Cam :	Cam C	
Main Air pressure :	0.824	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	49	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.13	kN	Max Punch ;	28
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	3
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	100016	Tablets			
A.W.C Counter :	98427	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	98427 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	LEVET 500mg STLC2B00
User ID :	pb97604	Batch NO. :	LCM2507350
Print Interval :	50000 Tablets	Running Time :	01 Hour 03 Min 24 Sec
Total Counter :	100016	Total Running Time :	2724 Hour 51 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	168	%	Manual ;	26	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1320000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	46.05	kN	No		
HEP :	25.0 %	44.28	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	36.14	kN	Yes 15	Times	
Ref :		35.43	kN			
LCP :	2.0 %	34.72	kN	Yes 15	Times	
LEP :	25.0 %	26.57	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	24.80	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	8.42	kN	Min :	8.36	kN	Punch NO.;	29
SD :	0.40	%	Max :	8.50	kN	Punch NO.;	37
Mean Main Pressure :	35.47	kN	Min :	33.98	kN	Punch NO.;	38
SD :	2.30	%	Max :	38.64	kN	Punch NO.;	7
Filling Depth :	Increase ;	20	Times	Decrease ;	16	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.60	mm	Pre Thickness ;	3.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.28	mm	Main Thickness ;	3.29	mm
Filling Depth :	8.40	mm	Current Cam :	Cam C	
Main Air pressure :	0.824	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	49	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.15	kN	Max Punch ;	28
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	3
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	100016	Tablets			
A.W.C Counter :	98427	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	98427 (100.0%)	Tablets			