

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	sj97904	Batch NO. :	MRM2502950
Print Interval :	50000 Tablets	Running Time :	00 Hour 38 Min 56 Sec
Total Counter :	100088	Total Running Time :	2738 Hour 23 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	14.26	kN	No		
HEP :	25.0 %	13.71	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.19	kN	Yes 15	Times	
Ref :		10.97	kN			
LCP :	2.0 %	10.75	kN	Yes 15	Times	
LEP :	25.0 %	8.23	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.68	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.73	kN	Min :	1.71	kN	Punch NO.;	21
		0.50	%	Max :	1.75	kN	Punch NO.;	12
Mean Main Pressure :		11.19	kN	Min :	10.24	kN	Punch NO.;	11
	SD :	3.60	%	Max :	12.17	kN	Punch NO.;	28
Filling Depth :	Increase ;	30	Times	Decrease ;	31	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.30	mm	Pre Thickness ;	4.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.70	mm	Main Thickness ;	2.71	mm
Filling Depth :	7.81	mm	Current Cam :	Cam C	
Main Air pressure :	0.830	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	47	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.06	kN	Max Punch ;	42
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.11	kN	Max Punch ;	45
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	100088	Tablets			
A.W.C Counter :	92946	Tablets			
HEP :	8 (0.0%)	Tablets	LEP :	33 (0.0%)	Tablets
GOOD :	92905 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	sj97904	Batch NO. :	MRM2502950
Print Interval :	50000 Tablets	Running Time :	00 Hour 38 Min 56 Sec
Total Counter :	100088	Total Running Time :	2738 Hour 23 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	26	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	14.45	kN	No		
HEP :	25.0 %	13.90	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.34	kN	Yes 15	Times	
Ref :		11.12	kN			
LCP :	2.0 %	10.90	kN	Yes 15	Times	
LEP :	25.0 %	8.34	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.78	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.86	kN	Min :	1.82	kN	Punch NO.;	12
SD :	0.80	%	Max :	1.89	kN	Punch NO.;	33
Mean Main Pressure :	11.24	kN	Min :	10.28	kN	Punch NO.;	11
SD :	3.70	%	Max :	12.54	kN	Punch NO.;	1
Filling Depth :	Increase ; 42	Times	Decrease ; 41	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.40	mm	Pre Thickness ;	4.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.80	mm	Main Thickness ;	2.81	mm
Filling Depth :	7.86	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.830	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	47	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.06	kN	Max Punch ;	42
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.11	kN	Max Punch ;	14
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	100088	Tablets			
A.W.C Counter :	92946	Tablets			
HEP :	8 (0.0%)	Tablets	LEP :	33 (0.0%)	Tablets
GOOD :	92905 (100.0%)	Tablets			