

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	pb97604	Batch NO. :	MRM2502950
Print Interval :	50000 Tablets	Running Time :	01 Hour 54 Min 33 Sec
Total Counter :	300144	Total Running Time :	2739 Hour 39 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	14.61	kN	No		
HEP :	25.0 %	14.05	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.46	kN	Yes 15	Times	
Ref :		11.24	kN			
LCP :	2.0 %	11.01	kN	Yes 15	Times	
LEP :	25.0 %	8.43	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.87	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.07	kN	Min :	0.97	kN	Punch NO.;	4
		5.10	%	Max :	1.22	kN	Punch NO.;	36
Mean Main Pressure :		11.41	kN	Min :	10.67	kN	Punch NO.;	8
	SD :	2.80	%	Max :	12.23	kN	Punch NO.;	36
Filling Depth :	Increase ;	91	Times	Decrease ;	95	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.70	mm	Main Thickness ;	2.71	mm
Filling Depth :	7.81	mm	Current Cam :	Cam C	
Main Air pressure :	0.797	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.28	kN	Max Punch ;	41
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.11	kN	Max Punch ;	22
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	300144	Tablets			
A.W.C Counter :	291300	Tablets			
HEP :	13 (0.0%)	Tablets	LEP :	33 (0.0%)	Tablets
GOOD :	291254 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	pb97604	Batch NO. :	MRM2502950
Print Interval :	50000 Tablets	Running Time :	01 Hour 54 Min 33 Sec
Total Counter :	300144	Total Running Time :	2739 Hour 39 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	26	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	13.61	kN	No		
HEP :	25.0 %	13.09	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.68	kN	Yes 15	Times	
Ref :		10.47	kN			
LCP :	2.0 %	10.26	kN	Yes 15	Times	
LEP :	25.0 %	7.85	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.33	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.59	kN	Min :	0.46	kN	Punch NO.;	27
SD :	11.30	%	Max :	0.72	kN	Punch NO.;	19
Mean Main Pressure :	10.51	kN	Min :	9.71	kN	Punch NO.;	18
SD :	4.20	%	Max :	11.45	kN	Punch NO.;	28
Filling Depth :	Increase ;	103	Times	Decrease ;	112	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.85	mm	Main Thickness ;	2.86	mm
Filling Depth :	7.79	mm	Current Cam :	Cam C	
Main Air pressure :	0.797	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.28	kN	Max Punch ;	16
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.11	kN	Max Punch ;	22
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	300144	Tablets			
A.W.C Counter :	291300	Tablets			
HEP :	13 (0.0%)	Tablets	LEP :	33 (0.0%)	Tablets
GOOD :	291254 (100.0%)	Tablets			