

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	vy190186	Batch NO. :	MRM2502950
Print Interval :	50000 Tablets	Running Time :	15 Hour 20 Min 00 Sec
Total Counter :	2450996	Total Running Time :	2753 Hour 5 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	106	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	12.77	kN	No		
HEP :	25.0 %	12.27	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.02	kN	Yes 15	Times	
Ref :		9.82	kN			
LCP :	2.0 %	9.62	kN	Yes 15	Times	
LEP :	25.0 %	7.36	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.87	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.72	kN	Min :	1.68	kN	Punch NO.;	6
SD :	0.90	%	Max :	1.77	kN	Punch NO.;	36
Mean Main Pressure :	9.67	kN	Min :	9.02	kN	Punch NO.;	39
SD :	2.70	%	Max :	10.26	kN	Punch NO.;	36
Filling Depth :	Increase ; 461	Times	Decrease ;	508	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.75	mm	Pre Thickness ;	3.76	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.99	mm	Main Thickness ;	3.00	mm
Filling Depth :	7.83	mm	Current Cam :	Cam C	
Main Air pressure :	0.824	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	32	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.11	kN	Max Punch ;	36
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.13	kN	Max Punch ;	50
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2450996	Tablets			
A.W.C Counter :	2440667	Tablets			
HEP :	82 (0.0%)	Tablets	LEP :	141 (0.0%)	Tablets
GOOD :	2440444 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	vy190186	Batch NO. :	MRM2502950
Print Interval :	50000 Tablets	Running Time :	15 Hour 20 Min 00 Sec
Total Counter :	2450996	Total Running Time :	2753 Hour 5 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	103	%	Manual ;	26	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	11.77	kN	No		
HEP :	25.0 %	11.32	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.23	kN	Yes 15	Times	
Ref :		9.05	kN			
LCP :	2.0 %	8.87	kN	Yes 15	Times	
LEP :	25.0 %	6.79	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.34	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.37	kN	Min :	1.30	kN	Punch NO.;	14
SD :	2.00	%	Max :	1.44	kN	Punch NO.;	38
Mean Main Pressure :	9.11	kN	Min :	8.40	kN	Punch NO.;	44
SD :	3.10	%	Max :	9.82	kN	Punch NO.;	22
Filling Depth :	Increase ; 503	Times	Decrease ;	519	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.65	mm	Pre Thickness ;	3.66	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.24	mm	Main Thickness ;	3.25	mm
Filling Depth :	7.83	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.824	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	32	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.10	kN	Max Punch ;	34
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.13	kN	Max Punch ;	50
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2450996	Tablets			
A.W.C Counter :	2440667	Tablets			
HEP :	82 (0.0%)	Tablets	LEP :	141 (0.0%)	Tablets
GOOD :	2440444 (100.0%)	Tablets			