

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	ms88737	Batch NO. :	MRM2503150
Print Interval :	50000 Tablets	Running Time :	00 Hour 37 Min 49 Sec
Total Counter :	100030	Total Running Time :	2766 Hour 32 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	106	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	12.46	kN	No		
HEP :	25.0 %	11.98	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.77	kN	Yes 15	Times	
Ref :		9.58	kN			
LCP :	2.0 %	9.39	kN	Yes 15	Times	
LEP :	25.0 %	7.19	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.71	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.89	kN	Min :	1.82	kN	Punch NO.;	5
SD :	1.70	%	Max :	1.96	kN	Punch NO.;	29
Mean Main Pressure :	9.73	kN	Min :	8.97	kN	Punch NO.;	39
SD :	4.60	%	Max :	10.98	kN	Punch NO.;	32
Filling Depth :	Increase ;	778	Times	Decrease ;	814	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.60	mm	Pre Thickness ;	3.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.99	mm	Main Thickness ;	3.00	mm
Filling Depth :	7.60	mm	Current Cam :	Cam C	
Main Air pressure :	0.745	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	36
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.11	kN	Max Punch ;	17
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	100030	Tablets			
A.W.C Counter :	98312	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	98310	Tablets			
	(100.0%)				

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	ms88737	Batch NO. :	MRM2503150
Print Interval :	50000 Tablets	Running Time :	00 Hour 37 Min 49 Sec
Total Counter :	100030	Total Running Time :	2766 Hour 32 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	103	%	Manual ;	26	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	12.18	kN	No		
HEP :	25.0 %	11.71	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.56	kN	Yes 15	Times	
Ref :		9.37	kN			
LCP :	2.0 %	9.18	kN	Yes 15	Times	
LEP :	25.0 %	7.03	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.56	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.78	kN	Min :	1.69	kN	Punch NO.;	18
SD :	2.50	%	Max :	1.89	kN	Punch NO.;	30
Mean Main Pressure :	9.42	kN	Min :	8.91	kN	Punch NO.;	18
SD :	3.70	%	Max :	10.53	kN	Punch NO.;	30
Filling Depth :	Increase ;	870	Times	Decrease ;	873	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.21	mm	Main Thickness ;	3.22	mm
Filling Depth :	7.75	mm	Current Cam :	Cam C	
Main Air pressure :	0.745	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.05	kN	Max Punch ;	33
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.11	kN	Max Punch ;	17
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	100030	Tablets			
A.W.C Counter :	98312	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	98310	Tablets			
	(100.0%)				