

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	pb97604	Batch NO. :	MRM2503150
Print Interval :	50000 Tablets	Running Time :	08 Hour 28 Min 57 Sec
Total Counter :	1300770	Total Running Time :	2774 Hour 22 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	115	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	12.26	kN	No		
HEP :	25.0 %	11.79	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.62	kN	Yes 15	Times	
Ref :		9.43	kN			
LCP :	2.0 %	9.24	kN	Yes 15	Times	
LEP :	25.0 %	7.08	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.60	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.84	kN	Min :	1.77	kN	Punch NO.;	51
SD :	1.50	%	Max :	1.93	kN	Punch NO.;	32
Mean Main Pressure :	9.39	kN	Min :	8.73	kN	Punch NO.;	37
SD :	3.60	%	Max :	10.42	kN	Punch NO.;	32
Filling Depth :	Increase ; 76	Times	Decrease ;	104	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.60	mm	Pre Thickness ;	3.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.94	mm	Main Thickness ;	2.95	mm
Filling Depth :	7.59	mm	Current Cam :	Cam C	
Main Air pressure :	0.799	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	21	Min			
Lower Punch Remain Time (S2):	40	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.07	kN	Max Punch ;	24
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.10	kN	Max Punch ;	2
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1300770	Tablets			
A.W.C Counter :	1295517	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	74 (0.0%)	Tablets
GOOD :	1295441 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	pb97604	Batch NO. :	MRM2503150
Print Interval :	50000 Tablets	Running Time :	08 Hour 28 Min 57 Sec
Total Counter :	1300770	Total Running Time :	2774 Hour 22 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	114	%	Manual ;	26	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	12.19	kN	No		
HEP :	25.0 %	11.72	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.56	kN	Yes 15	Times	
Ref :		9.37	kN			
LCP :	2.0 %	9.19	kN	Yes 15	Times	
LEP :	25.0 %	7.03	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.56	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.68	kN	Min :	1.61	kN	Punch NO.;	18
SD :	2.20	%	Max :	1.78	kN	Punch NO.;	30
Mean Main Pressure :	9.21	kN	Min :	8.70	kN	Punch NO.;	39
SD :	2.80	%	Max :	9.98	kN	Punch NO.;	30
Filling Depth :	Increase ; 68	Times	Decrease ; 74	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.17	mm	Main Thickness ;	3.18	mm
Filling Depth :	7.67	mm	Current Cam :	Cam C	
Main Air pressure :	0.799	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	21	Min			
Lower Punch Remain Time (S2):	40	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.07	kN	Max Punch ;	24
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.11	kN	Max Punch ;	2
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1300770	Tablets			
A.W.C Counter :	1295517	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	74 (0.0%)	Tablets
GOOD :	1295441 (100.0%)	Tablets			