

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	vy190186	Batch NO. :	MRM2503150
Print Interval :	50000 Tablets	Running Time :	14 Hour 54 Min 38 Sec
Total Counter :	2201102	Total Running Time :	2780 Hour 48 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	127	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	12.81	kN	No		
HEP :	25.0 %	12.32	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.05	kN	Yes 15	Times	
Ref :		9.86	kN			
LCP :	2.0 %	9.66	kN	Yes 15	Times	
LEP :	25.0 %	7.39	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.90	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.85	kN	Min :	1.79	kN	Punch NO.;	37
SD :	1.40	%	Max :	1.95	kN	Punch NO.;	32
Mean Main Pressure :	10.12	kN	Min :	9.36	kN	Punch NO.;	37
SD :	3.80	%	Max :	11.70	kN	Punch NO.;	32
Filling Depth :	Increase ;	172	Times	Decrease ;	222	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.60	mm	Pre Thickness ;	3.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.96	mm	Main Thickness ;	2.97	mm
Filling Depth :	7.61	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.777	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.06	kN	Max Punch ;	24
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	14
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2201102	Tablets			
A.W.C Counter :	2195660	Tablets			
HEP :	56 (0.0%)	Tablets	LEP :	75 (0.0%)	Tablets
GOOD :	2195529 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	vy190186	Batch NO. :	MRM2503150
Print Interval :	50000 Tablets	Running Time :	14 Hour 54 Min 38 Sec
Total Counter :	2201102	Total Running Time :	2780 Hour 48 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	122	%	Manual ;	26	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	13.47	kN	No		
HEP :	25.0 %	12.95	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.57	kN	Yes 15	Times	
Ref :		10.36	kN			
LCP :	2.0 %	10.15	kN	Yes 15	Times	
LEP :	25.0 %	7.77	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.25	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.78	kN	Min :	1.69	kN	Punch NO.;	7
SD :	2.20	%	Max :	1.87	kN	Punch NO.;	32
Mean Main Pressure :	10.43	kN	Min :	9.62	kN	Punch NO.;	11
SD :	3.90	%	Max :	11.55	kN	Punch NO.;	32
Filling Depth :	Increase ; 194	Times	Decrease ; 206	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	27	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.25	mm	Pre Thickness ;	3.26	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.10	mm	Main Thickness ;	3.11	mm
Filling Depth :	7.66	mm	Current Cam :	Cam C	
Main Air pressure :	0.777	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.06	kN	Max Punch ;	24
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.11	kN	Max Punch ;	14
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2201102	Tablets			
A.W.C Counter :	2195660	Tablets			
HEP :	56 (0.0%)	Tablets	LEP :	75 (0.0%)	Tablets
GOOD :	2195529 (100.0%)	Tablets			