

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	sj97904	Batch NO. :	MRM2503150
Print Interval :	50000 Tablets	Running Time :	01 Hour 58 Min 54 Sec
Total Counter :	3751836	Total Running Time :	2791 Hour 53 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	130	%	Manual ;	23	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	13.03	kN	No		
HEP :	25.0 %	12.53	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.22	kN	Yes 15	Times	
Ref :		10.02	kN			
LCP :	2.0 %	9.82	kN	Yes 15	Times	
LEP :	25.0 %	7.52	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.01	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.83	kN	Min :	1.80	kN	Punch NO.;	5
SD :	1.30	%	Max :	1.92	kN	Punch NO.;	29
Mean Main Pressure :	10.11	kN	Min :	9.25	kN	Punch NO.;	53
SD :	4.20	%	Max :	11.36	kN	Punch NO.;	29
Filling Depth :	Increase ; 308	Times	Decrease ;	370	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	29	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.60	mm	Pre Thickness ;	3.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.96	mm	Main Thickness ;	2.97	mm
Filling Depth :	7.59	mm	Current Cam :	Cam C	
Main Air pressure :	0.819	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.06	kN	Max Punch ;	26
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	53
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3751836	Tablets			
A.W.C Counter :	3746261	Tablets			
HEP :	58 (0.0%)	Tablets	LEP :	75 (0.0%)	Tablets
GOOD :	3746128 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500MG STMR2A00
User ID :	sj97904	Batch NO. :	MRM2503150
Print Interval :	50000 Tablets	Running Time :	01 Hour 58 Min 54 Sec
Total Counter :	3751836	Total Running Time :	2791 Hour 53 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	126	%	Manual ;	26	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	13.91	kN	No		
HEP :	25.0 %	13.37	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.91	kN	Yes 15	Times	
Ref :		10.70	kN			
LCP :	2.0 %	10.48	kN	Yes 15	Times	
LEP :	25.0 %	8.02	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.49	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.80	kN	Min :	1.70	kN	Punch NO.;	17
SD :	2.40	%	Max :	1.91	kN	Punch NO.;	26
Mean Main Pressure :	10.61	kN	Min :	9.92	kN	Punch NO.;	9
SD :	3.40	%	Max :	11.50	kN	Punch NO.;	26
Filling Depth :	Increase ; 396	Times	Decrease ;	398	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.25	mm	Pre Thickness ;	3.26	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.10	mm	Main Thickness ;	3.11	mm
Filling Depth :	7.70	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.819	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.05	kN	Max Punch ;	26
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	53
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3751836	Tablets			
A.W.C Counter :	3746261	Tablets			
HEP :	58 (0.0%)	Tablets	LEP :	75 (0.0%)	Tablets
GOOD :	3746128 (100.0%)	Tablets			