

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Gaba 600mg STKS1A00
User ID :	rp98927	Batch NO. :	KSM2500160
Print Interval :	50000 Tablets	Running Time :	01 Hour 51 Min 57 Sec
Total Counter :	200070	Total Running Time :	2830 Hour 53 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	23	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		1460000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	17.44	kN	No		
HEP :	25.0 %	16.77	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.68	kN	Yes 15	Times	
Ref :		13.41	kN			
LCP :	2.0 %	13.15	kN	Yes 15	Times	
LEP :	25.0 %	10.06	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.39	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.46	kN	Min :	3.33	kN	Punch NO.;	10
SD :	1.40	%	Max :	3.56	kN	Punch NO.;	23
Mean Main Pressure :	13.32	kN	Min :	12.62	kN	Punch NO.;	15
SD :	2.60	%	Max :	14.17	kN	Punch NO.;	36
Filling Depth :	Increase ; 11	Times	Decrease ; 19	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.20	mm	Pre Thickness ;	5.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.30	mm	Main Thickness ;	4.30	mm
Filling Depth :	11.28	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.818	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	44	Min			
Lower Punch Remain Time (S2):	23	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.07	kN	Max Punch ;	51
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.16	kN	Max Punch ;	44
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	200070	Tablets			
A.W.C Counter :	196648	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	196648 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Gaba 600mg STKS1A00
User ID :	rp98927	Batch NO. :	KSM2500160
Print Interval :	50000 Tablets	Running Time :	01 Hour 51 Min 57 Sec
Total Counter :	200070	Total Running Time :	2830 Hour 53 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	27	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		1460000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	18.46	kN	No		
HEP :	25.0 %	17.75	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.49	kN	Yes 15	Times	
Ref :		14.20	kN			
LCP :	2.0 %	13.92	kN	Yes 15	Times	
LEP :	25.0 %	10.65	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.94	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.02	kN	Min :	2.90	kN	Punch NO.;	33
		2.30	%	Max :	3.20	kN	Punch NO.;	21
Mean Main Pressure :	SD :	14.16	kN	Min :	13.14	kN	Punch NO.;	2
		3.00	%	Max :	14.98	kN	Punch NO.;	40
Filling Depth :	Increase ;	7	Times	Decrease ;	8	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.20	mm	Pre Thickness ;	5.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.48	mm	Main Thickness ;	4.48	mm
Filling Depth :	11.30	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.818	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	44	Min			
Lower Punch Remain Time (S2):	23	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.07	kN	Max Punch ;	51
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.16	kN	Max Punch ;	44
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	200070	Tablets			
A.W.C Counter :	196648	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	196648 (100.0%)	Tablets			