

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 20 mg,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2503320
Print Interval :	50000 Tablets	Running Time :	02 Hour 37 Min 01 Sec
Total Counter :	600272	Total Running Time :	2845 Hour 2 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		5500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	16.96	kN	No		
HEP :	25.0 %	16.30	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.30	kN	Yes 15	Times	
Ref :		13.04	kN			
LCP :	2.0 %	12.78	kN	Yes 15	Times	
LEP :	25.0 %	9.78	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.13	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.46	kN	Min :	1.44	kN	Punch NO.;	13
SD :	0.40	%	Max :	1.48	kN	Punch NO.;	53
Mean Main Pressure :	13.08	kN	Min :	11.09	kN	Punch NO.;	1
SD :	5.80	%	Max :	14.93	kN	Punch NO.;	6
Filling Depth :	Increase ; 25	Times	Decrease ; 32	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.22	mm	Main Thickness ;	1.22	mm
Filling Depth :	4.24	mm	Current Cam :	Cam B	
Main Air pressure :	0.766	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	22	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.05	kN	Max Punch ;	45
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.21	kN	Max Punch ;	75
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	600272	Tablets			
A.W.C Counter :	591433	Tablets			
HEP :	387 (0.1%)	Tablets	LEP :	16 (0.0%)	Tablets
GOOD :	591030 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 20 mg,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2503320
Print Interval :	50000 Tablets	Running Time :	02 Hour 37 Min 01 Sec
Total Counter :	600272	Total Running Time :	2845 Hour 2 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	34	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		5500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	16.68	kN	No		
HEP :	25.0 %	16.03	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.08	kN	Yes 15	Times	
Ref :		12.83	kN			
LCP :	2.0 %	12.57	kN	Yes 15	Times	
LEP :	25.0 %	9.62	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.98	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.06	kN	Min :	1.04	kN	Punch NO.;	32
		0.90	%	Max :	1.08	kN	Punch NO.;	4
Mean Main Pressure :		12.66	kN	Min :	10.44	kN	Punch NO.;	49
	SD :	8.30	%	Max :	15.07	kN	Punch NO.;	44
Filling Depth :	Increase ;	86	Times	Decrease ;	92	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.90	mm	Pre Thickness ;	1.90	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.37	mm	Main Thickness ;	1.37	mm
Filling Depth :	4.50	mm	Current Cam :	Cam B	
Main Air pressure :	0.766	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	22	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.05	kN	Max Punch ;	45
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.21	kN	Max Punch ;	75
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	600272	Tablets			
A.W.C Counter :	591433	Tablets			
HEP :	387 (0.1%)	Tablets	LEP :	16 (0.0%)	Tablets
GOOD :	591030 (99.9%)	Tablets			