

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 20 mg,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2503320
Print Interval :	50000 Tablets	Running Time :	05 Hour 51 Min 49 Sec
Total Counter :	1350754	Total Running Time :	2848 Hour 17 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	29	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		5500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	18.38	kN	No		
HEP :	25.0 %	17.67	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.42	kN	Yes 15	Times	
Ref :		14.14	kN			
LCP :	2.0 %	13.85	kN	Yes 15	Times	
LEP :	25.0 %	10.60	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.89	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.46	kN	Min :	1.45	kN	Punch NO.;	20
SD :	0.50	%	Max :	1.48	kN	Punch NO.;	6
Mean Main Pressure :	14.31	kN	Min :	12.31	kN	Punch NO.;	76
SD :	5.70	%	Max :	16.03	kN	Punch NO.;	65
Filling Depth :	Increase ; 41	Times	Decrease ; 65	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.22	mm	Main Thickness ;	1.22	mm
Filling Depth :	4.26	mm	Current Cam :	Cam B	
Main Air pressure :	0.764	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.05	kN	Max Punch ;	44
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.19	kN	Max Punch ;	75
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1350754	Tablets			
A.W.C Counter :	1341288	Tablets			
HEP :	671 (0.1%)	Tablets	LEP :	354 (0.0%)	Tablets
GOOD :	1340263 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 20 mg,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2503320
Print Interval :	50000 Tablets	Running Time :	05 Hour 51 Min 49 Sec
Total Counter :	1350754	Total Running Time :	2848 Hour 17 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	34	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		5500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	18.39	kN	No		
HEP :	25.0 %	17.68	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.43	kN	Yes 15	Times	
Ref :		14.15	kN			
LCP :	2.0 %	13.86	kN	Yes 15	Times	
LEP :	25.0 %	10.61	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.90	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.05	kN	Min :	1.03	kN	Punch NO.;	2
SD :	0.80	%	Max :	1.07	kN	Punch NO.;	29
Mean Main Pressure :	13.96	kN	Min :	12.04	kN	Punch NO.;	11
SD :	6.90	%	Max :	15.89	kN	Punch NO.;	4
Filling Depth :	Increase ;	227	Times	Decrease ;	239	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.90	mm	Pre Thickness ;	1.90	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.37	mm	Main Thickness ;	1.37	mm
Filling Depth :	4.67	mm	Current Cam :	Cam B	
Main Air pressure :	0.764	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.05	kN	Max Punch ;	44
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.19	kN	Max Punch ;	75
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1350754	Tablets			
A.W.C Counter :	1341288	Tablets			
HEP :	671 (0.1%)	Tablets	LEP :	354 (0.0%)	Tablets
GOOD :	1340263 (99.9%)	Tablets			