

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 20 mg,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2503320
Print Interval :	50000 Tablets	Running Time :	21 Hour 39 Min 53 Sec
Total Counter :	5003212	Total Running Time :	2864 Hour 6 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	32	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		5500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	18.31	kN	No		
HEP :	25.0 %	17.60	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.36	kN	Yes 15	Times	
Ref :		14.08	kN			
LCP :	2.0 %	13.80	kN	Yes 15	Times	
LEP :	25.0 %	10.56	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.86	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.41	kN	Min :	1.39	kN	Punch NO.;	2
SD :	0.60	%	Max :	1.43	kN	Punch NO.;	36
Mean Main Pressure :	13.98	kN	Min :	11.88	kN	Punch NO.;	5
SD :	6.30	%	Max :	16.00	kN	Punch NO.;	40
Filling Depth :	Increase ; 166	Times	Decrease ;	212	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.22	mm	Main Thickness ;	1.22	mm
Filling Depth :	4.72	mm	Current Cam :	Cam B	
Main Air pressure :	0.789	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.20	kN	Max Punch ;	51
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.30	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	5003212	Tablets			
A.W.C Counter :	4988101	Tablets			
HEP :	2399 (0.0%)	Tablets	LEP :	1400 (0.0%)	Tablets
GOOD :	4984302 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Panto 20 mg,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2503320
Print Interval :	50000 Tablets	Running Time :	21 Hour 39 Min 53 Sec
Total Counter :	5003212	Total Running Time :	2864 Hour 6 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	38	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		5500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	17.43	kN	No		
HEP :	25.0 %	16.76	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.68	kN	Yes 15	Times	
Ref :		13.41	kN			
LCP :	2.0 %	13.14	kN	Yes 15	Times	
LEP :	25.0 %	10.06	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.39	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.98	kN	Min :	0.95	kN	Punch NO.;	63
SD :	1.00	%	Max :	1.00	kN	Punch NO.;	1
Mean Main Pressure :	13.61	kN	Min :	11.18	kN	Punch NO.;	21
SD :	7.90	%	Max :	15.82	kN	Punch NO.;	4
Filling Depth :	Increase ;	1290	Times	Decrease ;	1301	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.90	mm	Pre Thickness ;	1.90	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.35	mm	Main Thickness ;	1.35	mm
Filling Depth :	4.90	mm	Current Cam :	Cam B	
Main Air pressure :	0.789	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.20	kN	Max Punch ;	51
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.29	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	5003212	Tablets			
A.W.C Counter :	4988178	Tablets			
HEP :	2399 (0.0%)	Tablets	LEP :	1400 (0.0%)	Tablets
GOOD :	4984379 (99.9%)	Tablets			